



# SAFETY DATA SHEET

Revisione n. 4  
Data revisione 28/05/2015  
Pagina 1 / 15  
Cod. 600

## HIGH SPEED CHAIN

### 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Codice M 600  
Denominazione HIGH SPEED CHAIN

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Grasso spray per catene

#### 1.3 Details of the supplier of the safety data sheet

Resp. dell'immissione sul mercato: MAROIL S.r.l.  
Loc. Ponte alla Ciliegia – Marginone  
55011 Altopascio (LU)  
Tel. 0583 28731  
Fax 0583 286542

e-mail della persona competente,  
responsabile della scheda dati di  
sicurezza marco@bardahl.it

#### 1.4. Emergency telephone number

Per informazioni urgenti rivolgersi a

**Numeri telefonici dei principali Centri Antiveleni italiani (attivi 24/24 ore)**  
Centro Antiveleni di Pavia 0382 24444 (CAV IRCCS Fondazione Maugeri - Pavia)  
Centro Antiveleni di Milano 02 66101029 (CAV Ospedale Niguarda Ca' Granda - Milano)  
Centro Antiveleni di Bergamo 800 883300 (CAV Ospedali Riuniti - Bergamo)  
Centro Antiveleni di Firenze 055 7947819 (CAV Ospedale Careggi - Firenze)  
Centro Antiveleni di Roma 06 3054343 (CAV Policlinico Gemelli - Roma)  
Centro Antiveleni di Roma 06 49978000 (CAV Policlinico Umberto I - Roma)  
Centro Antiveleni di Napoli 081 7472870 (CAV Ospedale Cardarelli - Napoli)

## 2. HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

**In compliance with EC regulation No. 1272/2008 and its amendments.**

Flammable aerosol, Category 1 (Aerosol 1, H222 - H229).

Skin irritation, Category 2 (Skin Irrit. 2, H315).

Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H336).

Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

**In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.**

Extremely flammable (F+, R 12).

Skin irritation (Xi, R 38).

Vapours may cause drowsiness and dizziness (R 67).

Aquatic environmental hazard, chronic toxicity: harmful (R 52/53).

### 2.2. Label elements

Mixture for aerosol application.

**Maroil s.r.l. – Bardahl Italia**

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542

www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio

Partita IVA 01583810468 – Codice Fiscale / Registro Imprese 00160000477 – Cap. Soc. € 98.800,00 – R.E.A. di Lucca n. 84045

# SAFETY DATA SHEET

## HIGH SPEED CHAIN

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS 07



GHS 02

Signal Word :  
DANGER

Product identifiers :

EC 931-254-9 HYDROCARBONS, C6, ISOALKANES, < 5 % N-HEXANE

Hazard statements :

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements - General :

P102 Keep out of reach of children.

Precautionary statements - Prevention :

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P271 Use only outdoors or in a well-ventilated area.

Precautionary statements - Response :

P302 + P352 IF ON SKIN: Wash with plenty of water/...

Precautionary statements - Storage :

P403 Store in a well-ventilated place.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

### 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC)  $\geq 0.1\%$  published by the European CHemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture satisfies neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

Intentional misuse of the preparation by concentrating and inhaling the vapours can be harmful or fatal.

### Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542  
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio  
Partita IVA 01583810468 – Codice Fiscale / Registro Imprese 00160000477 – Cap. Soc. € 98.800,00 – R.E.A. di Lucca n. 84045



# SAFETY DATA SHEET

Revisione n. 4  
Data revisione 28/05/2015  
Pagina 3 / 15  
Cod. 600

## HIGH SPEED CHAIN

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.2. Mixtures

##### Composition :

| Identification  | (CE) 1272/2008   | 67/548/CEE   | Note     | %              |
|---|--|--|----------|----------------|
| INDEX: 931_254_9<br>EC: 931-254-9<br>REACH: 01-2119484651-34<br>IDROCARBURI, C6,<br>ISOALCANI, <5%<br>N-ESANO         | GHS07, GHS09,<br>GHS08,<br>GHS02<br>Dgr<br>Flam. Liq. 2, H225<br>Asp. Tox. 1, H304<br>Skin Irrit. 2, H315<br>STOT SE 3, H336<br>Aquatic Chronic 2,<br>H411 | Xn,N,F<br>Xn;R65<br>Xi;R38<br>N;R51/53<br>F;R11<br>R67 |          | 10 <= x % < 25 |
| INDEX: 601-004-00-0<br>CAS: 106-97-8<br>EC: 203-448-7<br>REACH: 01-2119474691-32<br>BUTANO (< 0.1 %<br>1,3-BUTADIENO) | GHS02, GHS04<br>Dgr<br>Flam. Gas 1, H220   | F+<br>F+;R12   | C<br>[1] | 10 <= x % < 25 |
| INDEX: 601-004-00-0<br>CAS: 75-28-5<br>EC: 200-857-2<br>REACH: 01-2119474691-32                                       | GHS02, GHS04<br>Dgr<br>Flam. Gas 1, H220   | F+<br>F+;R12   | C<br>[1] | 10 <= x % < 25 |
| INDEX: 601-003-00-5<br>CAS: 74-98-6<br>EC: 200-827-9<br>REACH: 01-2119486944-21<br>PROPANO                            | GHS02, GHS04<br>Dgr<br>Flam. Gas 1, H220   | F+<br>F+;R12   | [1]      | 10 <= x % < 25 |

##### Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

### 4. FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.  
NEVER induce swallowing by an unconscious person.

#### 4.1. Description of first aid measures

##### In the event of exposure by inhalation :

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

##### Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542  
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio  
Partita IVA 01583810468 – Codice Fiscale / Registro Imprese 00160000477 – Cap. Soc. € 98.800,00 – R.E.A. di Lucca n. 84045



# SAFETY DATA SHEET

Revisione n. 4  
Data revisione 28/05/2015  
Pagina 4 / 15  
Cod. 600

---

## HIGH SPEED CHAIN

---

### In the event of splashes or contact with eyes :

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists : Get medical advice/attention.

### In the event of splashes or contact with skin :

Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.

### In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor. Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

### 4.2. Most important symptoms and effects, both acute and delayed

See section 11.

### 4.3. Indication of any immediate medical attention and special treatment needed

If you feel unwell, seek medical advice (show the label if possible). If symptoms persist, always call a doctor.

## 5. FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

### 5.1. Extinguishing media

If the aerosols are exposed to a fire : keep containers cool by spraying with water from a protected position.

### Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO<sub>2</sub>)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

### Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

### 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

### Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542  
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio  
Partita IVA 01583810468 – Codice Fiscale / Registro Imprese 00160000477 – Cap. Soc. € 98.800,00 – R.E.A. di Lucca n. 84045



# SAFETY DATA SHEET

Revisione n. 4  
Data revisione 28/05/2015  
Pagina 5 / 15  
Cod. 600

---

## HIGH SPEED CHAIN

---

In a fire or if heated, a pressure increase will occur and the container may burst. Bursting aerosol containers may be propelled from a fire at high speed. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

### 5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

If possible, stop the product stream. Spray from a protected position till the containers are cool. If possible, take the aerosols outside. Keep public on a distance.

## 6. ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

#### For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid inhaling the vapors. Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

#### For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

### 6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Use drums to dispose of collected waste in compliance with current regulations (see section 13).

### 6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

### 6.4. Reference to other sections

No data available.

## 7. HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

### 7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Remove contaminated clothing and protective equipment before entering eating areas.

### Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542

www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio

Partita IVA 01583810468 – Codice Fiscale / Registro Imprese 00160000477 – Cap. Soc. € 98.800,00 – R.E.A. di Lucca n. 84045



# SAFETY DATA SHEET

Revisione n. 4  
Data revisione 28/05/2015  
Pagina 6 / 15  
Cod. 600

---

## HIGH SPEED CHAIN

---

### Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air. Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn, even after use.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

### Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Do not breathe in aerosols.

Avoid inhaling vapors.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Packages which have been opened must be reclosed carefully and stored in an upright position.

### Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

Never open the packages under pressure.

### 7.2. Conditions for safe storage, including any incompatibilities

No data available.

### Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Storage in a dry, frost-free and well ventilated place.

### Packaging

Always keep in packaging made of an identical material to the original.

### 7.3. Specific end use(s)

No data available.

### Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542

www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio

Partita IVA 01583810468 – Codice Fiscale / Registro Imprese 00160000477 – Cap. Soc. € 98.800,00 – R.E.A. di Lucca n. 84045



# SAFETY DATA SHEET

Revisione n. 4  
Data revisione 28/05/2015  
Pagina 7 / 15  
Cod. 600

## HIGH SPEED CHAIN

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control parameters

##### Occupational exposure limits :

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

| CAS      | TWA :    | STEL : | Ceiling : | Definizione : | Criteri : |
|----------|----------|--------|-----------|---------------|-----------|
| 106-97-8 | 1000 ppm | -      | -         | -             | -         |
| 75-28-5  | 1000 ppm | -      | -         | -             | -         |
| 74-98-6  | 1000 ppm | -      | -         | -             | -         |

- Germania - AGW (BAuA - TRGS 900, 21/06/2010) :

| CAS      | VME :      | VME :      | Superamento | Note |
|----------|------------|------------|-------------|------|
| 106-97-8 | 1000 ml/m3 | 2400 mg/m3 | 4(II)       | DFG  |
| 75-28-5  | 1000 ml/m3 | 2400 mg/m3 | 4(II)       | DFG  |
| 74-98-6  | 1000 ml/m3 | 1800 mg/m3 | 4(II)       | DFG  |

- Francia (INRS - ED984 :2008) :

| CAS      | VME-ppm : | VME-mg/m3 : | VLE-ppm : | VLE-mg/m3 : | Notes : | TMP N° : |
|----------|-----------|-------------|-----------|-------------|---------|----------|
| 106-97-8 | 800       | 1900        | -         | -           | -       | -        |

Idrocarburi, C6, isoalcani, < 5 % n-esano : RCP-TWA-mg/m<sup>3</sup> : 1200; RCP-TWA-ppm : 381

**Derived no effect level (DNEL) or derived minimum effect level (DMEL):**

IDROCARBURI, C6, ISOALCANI, <5% N-ESANO

#### Final use:

Exposure method:  
Potential health effects:  
DNEL :  
Exposure method:  
Potential health effects:  
DNEL :

#### Workers.

Dermal contact.  
Long term systemic effects.  
13964 mg/kg body weight/day  
Inhalation.  
Long term systemic effects.  
5306 mg of substance/m<sup>3</sup>

#### Final use:

Exposure method:  
Potential health effects:  
DNEL :  
Exposure method:  
Potential health effects:  
DNEL :  
Exposure method:  
Potential health effects:  
DNEL :

#### Consumers.

Ingestion.  
Long term systemic effects.  
1301 mg/kg body weight/day  
Dermal contact.  
Long term systemic effects.  
1377 mg/kg body weight/day  
Inhalation.  
Long term systemic effects.  
1137 mg of substance/m<sup>3</sup>

### 8.2. Exposure controls

#### Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.  
Store personal protective equipment in a clean place, away from the work area.  
Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

#### Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542  
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio  
Partita IVA 01583810468 – Codice Fiscale / Registro Imprese 00160000477 – Cap. Soc. € 98.800,00 – R.E.A. di Lucca n. 84045



# SAFETY DATA SHEET

Revisione n. 4  
Data revisione 28/05/2015  
Pagina 8 / 15  
Cod. 600

---

## HIGH SPEED CHAIN

---

### - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

Do not spray in the direction of the eyes.

### - Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- PVA (Polyvinyl alcohol)

Recommended properties :

- Impervious gloves in accordance with standard EN374

Not necessary at efficient use. Wash your hands after contact with skin.

### - Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

Not necessary at efficient use. Wash skin that has been in contact with the product, with water and soap.

### - Respiratory protection

Avoid breathing vapours.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Type of FFP mask :

Wear a disposable half-mask aerosol filter in accordance with standard EN149.

Category :

- FFP1

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

Particle filter according to standard EN143 :

- P1 (White)

Do not breathe spray. Use only in well-ventilated areas.

### Exposure controls linked to environmental protection

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542

www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio

Partita IVA 01583810468 – Codice Fiscale / Registro Imprese 00160000477 – Cap. Soc. € 98.800,00 – R.E.A. di Lucca n. 84045





# SAFETY DATA SHEET

Revisione n. 4  
Data revisione 28/05/2015  
Pagina 9 / 15  
Cod. 600

## HIGH SPEED CHAIN

### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1. Information on basic physical and chemical properties

##### General information :

Physical state : Fluid liquid.  
Spray.  
Odour : Specific

##### Important health, safety and environmental information

pH : Not relevant.  
Boiling point/boiling range : Not relevant.  
Vapour pressure (50°C) : Not relevant.  
Density : 0.673  
Water solubility : Insoluble.  
Melting point/melting range : Not relevant.  
Self-ignition temperature : Not relevant.  
Decomposition point/decomposition range : Not relevant.  
Chemical combustion heat : Not specified.  
Inflammation time : Not specified.  
Deflagration density : Not specified.  
Inflammation distance : Not specified.  
Flame height : Not specified.  
Flame duration : Not specified.  
Flash point : < 0 °C  
Flammability : Extremely flammable

#### 9.2. Altre informazioni

VOC (g/l) : 465.72  
Pressure at 20°C : ± 3.5 bar

### 10. STABILITY AND REACTIVITY

#### 10.1. Reactivity

No data available.

#### 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

#### 10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

Under normal conditions of storage and use, hazardous reactions will not occur.

#### 10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :  
- heat

#### Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542  
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio  
Partita IVA 01583810468 – Codice Fiscale / Registro Imprese 00160000477 – Cap. Soc. € 98.800,00 – R.E.A. di Lucca n. 84045



# SAFETY DATA SHEET

Revisione n. 4  
Data revisione 28/05/2015  
Pagina 10 / 15  
Cod. 600

## HIGH SPEED CHAIN

Protect from sunlight and do not expose to temperatures exceeding 50°C. Keep away from heat and sources of ignition. Storage in a dry, frost-free and well ventilated place.

### 10.5. Incompatible materials

No materials known by which a dangerous reaction can appear.

### 10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

The product is stable. Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## 11. TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Splashes in the eyes may cause irritation and reversible damage

Narcotic effects may occur, such as drowsiness, narcosis, decreased alertness, loss of reflexes, lack of coordination or dizziness.

Effects may also occur in the form of violent headaches or nausea, judgement disorder, giddiness, irritability, fatigue or memory disturbance.

#### 11.1.1. Substances

##### Acute toxicity :

HYDROCARBONS, C6, ISOALKANES, < 5 % N-HEXANE

Oral route : DL50 = 16750 mg/kg  
Species : rat  
OECD Guideline 401 (Acute Oral Toxicity)

Dermal route : DL50 = 3350 mg/kg  
Species : rabbit  
OECD Guideline 402 (Acute Dermal Toxicity)

Inhalation route : CL50 = 259354 mg/m<sup>3</sup>  
Species : rat  
OECD Guideline 403 (Acute Inhalation Toxicity)

##### Skin corrosion/skin irritation :

##### Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542  
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio  
Partita IVA 01583810468 – Codice Fiscale / Registro Imprese 00160000477 – Cap. Soc. € 98.800,00 – R.E.A. di Lucca n. 84045



# SAFETY DATA SHEET

Revisione n. 4  
Data revisione 28/05/2015  
Pagina 11 / 15  
Cod. 600

---

## HIGH SPEED CHAIN

---

Hydrocarbons, C6, isoalkanes, < 5 % n-hexane : Moderately irritating to skin with prolonged exposure.

**Serious damage to eyes/eye irritation :**

Hydrocarbons, C6, isoalkanes, < 5 % n-hexane : May cause mild, short-lasting discomfort to eyes.

**Respiratory or skin sensitisation :**

Hydrocarbons, C6, isoalkanes, < 5 % n-hexane : Not likely to be sensitizing.

**Germ cell mutagenicity :**

HYDROCARBONS, C6, ISOALKANES, < 5 % N-HEXANE  
No mutagenic effect.

**Carcinogenicity :**

HYDROCARBONS, C6, ISOALKANES, < 5 % N-HEXANE  
Carcinogenicity Test : Negative.  
No carcinogenic effect.

**Reproductive toxicant :**

HYDROCARBONS, C6, ISOALKANES, < 5 % N-HEXANE  
No toxic effect for reproduction

**Specific target organ systemic toxicity - single exposure :**

Hydrocarbons, C6, isoalkanes, < 5 % n-hexane : May cause drowsiness or dizziness.

**Specific target organ systemic toxicity - repeated exposure :**

Hydrocarbons, C6, isoalkanes, < 5 % n-hexane : Not likely to cause organ damage..

**11.1.2. Mixture**

No toxicological data available for the mixture.

## 12. ECOLOGICAL INFORMATION

Harmful to aquatic life with long lasting effects.  
The product must not be allowed to run into drains or waterways.

### 12.1. Toxicity

#### 12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

#### 12.2. Persistence and degradability

Butane/Isobutane/Propane : Expected to be readily biodegradable.  
Hydrocarbons, C6, isoalkanes, < 5 % n-hexane : Expected to be readily biodegradable. Transformation due to hydrolysis and due to photolysis is not expected to be significant. Expected to degrade rapidly in air.

##### 12.2.1. Substances

HYDROCARBONS, C6, ISOALKANES, < 5 % N-HEXANE  
Biodegradability : Fast degrading.

### 12.3. Bioaccumulative potential

**Maroil s.r.l. – Bardahl Italia**

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542  
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio  
Partita IVA 01583810468 – Codice Fiscale / Registro Imprese 00160000477 – Cap. Soc. € 98.800,00 – R.E.A. di Lucca n. 84045



# SAFETY DATA SHEET

Revisione n. 4  
Data revisione 28/05/2015  
Pagina 12 / 15  
Cod. 600

---

## HIGH SPEED CHAIN

---

Butane/Isobutane/Propane : Not expected to be dangerous for the aquatic environment.  
Hydrocarbons, C6, isoalkanes, < 5 % n-hexane : Not determined.

### 12.4. Mobility in soil

Butane/Isobutane/Propane : If released into the environment, the product will rapidly disperse into the atmosphere where it will undergo photochemical degradation.

Hydrocarbons, C6, isoalkanes, < 5 % n-hexane : Highly volatile, will spread rapidly in air. It is not expected to extract to the sediment and the fraction fixed substances in the waste water.

### 12.5. Results of PBT and vPvB assessment

Hydrocarbons, C6, isoalkanes, < 5 % n-hexane : PBT/vPvT : No.

### 12.6. Other adverse effects

No data available.

## 13. DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

### 13.1. Waste treatment methods

Do not pour into drains or waterways.

#### Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

#### Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

## 14. TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2013 - IMDG 2012 - ICAO/IATA 2014).

### 14.1. UN Number

1950

### 14.2. UN proper shipping name

UN1950=AEROSOLS, flammable

### 14.3. Transport hazard class(es)

- Classification:

#### Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542

www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio

Partita IVA 01583810468 – Codice Fiscale / Registro Imprese 00160000477 – Cap. Soc. € 98.800,00 – R.E.A. di Lucca n. 84045

# SAFETY DATA SHEET

## HIGH SPEED CHAIN



2.1

ADR/RID Label : Limited Quantity : 2.1 is not applicable.

#### 14.4. Gruppo d'imballaggio

-

#### 14.5. Environmental hazards

#### 14.6. Special precautions for user

| ADR/RID | Class | Code | Pack. gr. | Label | Identif. | LQ  | Provis.         | EQ | Cat. | Tunnel |
|---------|-------|------|-----------|-------|----------|-----|-----------------|----|------|--------|
|         | 2     | 5F   | -         | 2.1   | -        | 1 L | 190 327 344 625 | E0 | 2    | D      |

| IMDG | Class | 2° Label | Pack. gr. | LQ    | Ems      | Provis.                | EQ |
|------|-------|----------|-----------|-------|----------|------------------------|----|
|      | 2.1   | See SP63 | -         | SP277 | F-D, S-U | 63 190 277 327 344 959 | E0 |

| IATA | Class | 2° Label | Pack. gr. | Passager | Passager | Cargo | Cargo  | Note                                      | EQ |
|------|-------|----------|-----------|----------|----------|-------|--------|---|----|
|      | 2.1   | -        | -         | 203      | 75 kg    | 203   | 150 kg | A 145<br>A 167<br>A 145<br>A 167<br>A 802 | E0 |
|      | 2.1   | -        | -         | Y203     | 30 kg G  | -     | -      | A 145<br>A 167<br>A 802                   | E0 |

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.  
For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No data available.

## 15. REGULATORY INFORMATION

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture - Classification and labelling information included in section 2:

The following regulations have been used:

- Directive 67/548/EEC and its adaptations
- Directive 1999/45/EC and its adaptations
- Directive 75/734/CEE modified by directive 2013/10/UE
- EU Regulation No. 1272/2008 amended by EU Regulation No. 487/2013.

#### Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542  
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio  
Partita IVA 01583810468 – Codice Fiscale / Registro Imprese 00160000477 – Cap. Soc. € 98.800,00 – R.E.A. di Lucca n. 84045

# SAFETY DATA SHEET

## HIGH SPEED CHAIN

- EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 944/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 605/2014.

**- Container information:**

No data available.

**- Particular provisions :**

No data available.

### 15.2. Chemical safety assessment

A chemical safety assessment has been carried out for the following products or for the substances in these products : Hydrocarbons, C6, isoalkanes, < 5 % n-hexane

## 16. OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

**In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.**

Hazard Symbols :



Irritant



Extremely flammable

Risk phrase :

R 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 38 Irritating to skin.

R 12 Extremely flammable.

R 67 Vapours may cause drowsiness and dizziness.

Safety phrase :

S 16 Keep away from sources of ignition - No smoking.

S 2 Keep out of the reach of children.

S 23 Do not breathe vapour.

S 23 Do not breathe vapour/spray.

S 23 Do not breathe spray.

S 46 If swallowed, seek medical advice immediately and show this container or label.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C.

**Maroil s.r.l. – Bardahl Italia**

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542

www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio

Partita IVA 01583810468 – Codice Fiscale / Registro Imprese 00160000477 – Cap. Soc. € 98.800,00 – R.E.A. di Lucca n. 84045



# SAFETY DATA SHEET

Revisione n. 4  
Data revisione 28/05/2015  
Pagina 15 / 15  
Cod. 600

---

## HIGH SPEED CHAIN

---

Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

S 37 Wear suitable gloves.

S 51 Use only in well-ventilated areas.

S 64 If swallowed, rinse mouth with water (only if the person is conscious).

### Title for H, EUH and R indications mentioned in section 3 :

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

R 11 Highly flammable.

R 12 Extremely flammable.

R 38 Irritating to skin.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 65 Harmful: may cause lung damage if swallowed.

R 67 Vapours may cause drowsiness and dizziness.

### Abbreviations :

DNEL : Derived No-Effect Level

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS02 : Flame

GHS07 : Exclamation mark

### Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542

www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio

Partita IVA 01583810468 – Codice Fiscale / Registro Imprese 00160000477 – Cap. Soc. € 98.800,00 – R.E.A. di Lucca n. 84045