



TECHNICAL DATA SHEET
v042015

XTC 10W40

DESCRIPTION

High performance, synthetic motor oil for petrol and diesel engines, turbo-charged or not. This engine oil is suitable for extended oil drain intervals. Excellent protection at cold start and at different temperatures. It offers an excellent protection at cold start and at any engine temperature.

APPLICATION

Bardahl XTC 10w40 can be used all year long and in the most difficult operating conditions. Offers a good fluidity at low temperature.

SPECIFICATIONS

This product offers the following performance level:

ACEA	A3 B4 -12
API	SL / CF
VW	502.00 / 505.00
MB	229.1

PROPERTIES

- ✓ Offers a stable viscosity.
- ✓ Makes cold start easier.
- ✓ Provides a good resistance to oxidation.

SADAPS BARDAHL ADDITIVES & LUBRICANTS

ZI Tournai Ouest - 3, Rue du Mont des Carliers - B-7522 TOURNAI
Tél. : +32 69 590 360 - Fax : +32 69 590 361 - www.bardahlfrance.com



XTC 10W40

TECHNICAL DATA

Density at 15 °C	Kg/l	0,869
Viscosity at -35 °C	mPa.s	6170
Viscosity at 40 °C	mm ² /s	90
Viscosity at 100 °C	mm ² /s	13,5
Viscosity Index		152
Flash point COC, °C	°C	224
Pour point, °C	°C	-42
TBN alcalinity	mgKOH/g	10,2
Sulphated ash contents	%	1,29

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 36 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

36240	6 x 400 ML
36241	12 x 1 L
36243	3 x 5 L
36248	20 L
36244	60 L
36247	205 L

SADAPS BARDAHL ADDITIVES & LUBRICANTS