



# ATF VI

## DESCRIPTION

High quality and high viscosity synthetic automatic fluid, formulated for automatic transmissions, power steering systems, torque converters and other hydraulic specific applications.

## APPLICATION

Bardahl ATF VI provides an excellent stability and fluidity at low temperature. Ideal for cold starting and extended lifespan. Bardahl ATF VI can be used when an ATF fluid showing superior performance to Dexron II and III is recommended. **CAUTION: Bardahl ATF VI CANNOT BE USED IN CVT AND DCT TRANSMISSIONS, or when the FORD Type F/G performance level is required.**

**SPECIFICATIONS** - this product offers the following performance level:

CHRYSLER DODGE MOPAR	AS68RC (Type IV) ATF+/-2/+3/+4
BMW / Mini	ETL-7045/ 7045E/ 8072B/ LA2634/ Mini cooper T-IV
MERCEDES-BENZ	236.1 / 236.5 / 236.7 / 236.8 / 236.9 / 236.41
GM/ OPEL	DEXRON VI / IID/IIIE/IIIG/IIIH/TASA
MITSUBISHI	SK/SP-II/SP-III/SP-IV/AW/J2/J3/ATF PA
VW (VAG)	G-0055-025/ G-052-162
PORSCHE	ATF 3403 M115/Type IV
FORD	MERCON LV / Mercon/WSS-M2C138-CJ/166-H/922-A1/924-A
NISSAN	MATIC C/ D/ J/ K/ S
HONDA ACURA	DW-1/ ATF Z-1/ Premium (except in CVT)
MAZDA	ATF DII/M-III/M-V/FZ/F-1/S-1/N-1/3317
HYUNDAI / KIA	SP-II/SP-III/SP-IV/SP-IV M/SP-IV RR / JWS 3314/9683
ALLISON	TES 228 C3/C4
SUZUKI	ATF 3309/3314/3317/2326/2384K
SUBARU	ATF/ATF 5AT/ATF HP
AISIN WARNER	JWS 3309/3324(W.S)
TOYOTA	ATF T-III/ T-IV/ WS
ISUZU BESCO	ATF II/ III
JAGUAR	ATF 3403 M115/ JLM 20238
JASO	M315-2013 1A/1A-LV/2A
JWS	3309 (IV)/ 3324(W.S)
VOLVO	1161540/97340
ZF	5HP 18FL/ 19FL/ 24A/ 30/ 4HP 20 / TE-ML 11A/11B
VOITH	H55.6335

## SADAPS BARD AHL ADDITIVES & LUBRICANTS



## TECHNICAL DATA SHEET V112016

### PROPERTIES

- ✓ Has a high viscosity index ensuring a very good stability.
- ✓ Extended lifespan compared with other Dexron type fluids.
- ✓ Has a very low pour point.
- ✓ Offers an excellent stability at different temperatures.
- ✓ Offers a very good protection against oxidation.
- ✓ Provides anti wear, anticorrosion and antifoam properties.
- ✓ Contains antifriction additives for a smooth and silent change of gear.
- ✓ Does not damage synthetic gaskets.
- ✓ Circulates quickly at cold start.
- ✓ Red colour.

### TECHNICAL DATA

Density at 15 °C	Kg/l	0,843
Viscosity 40 °C	mm <sup>2</sup> /s	29,6
Viscosity 100 °C	mm <sup>2</sup> /s	5,90
Viscosity Index		149
Flash point COC, °C	°C	212
Pour point, °C	°C	-51
TBN alcalinity	mgKOH/g	2,7

### RECOMMENDATIONS

**Handling :** any safety information related to the handling and use of this product are gathered in the Safety Data Sheet. Always check the manufacturer car manual before use.

**Storage :** it is recommended to use the product within 36 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

### REFERENCES & AVAILABILITIES

36591	12 x 1 L
36593	3 x 5 L
36598	20 L
36594	60 L
36597	205 L

#### SADAPS BARDAHL ADDITIVES & LUBRICANTS

ZI Tournai Ouest - 3, Rue du Mont des Carliers - B-7522 TOURNAI  
Tél. : +32 69 590 360 - Fax : +32 69 590 361 - [www.bardahlfrance.com](http://www.bardahlfrance.com)