



ENGINE STOP LEAK BARD AHL

Safety Data Sheet

Date of issue: 30/12/2015

Revision date: 30/12/2015

Supersedes: 23/11/2015

Version: 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : ENGINE STOP LEAK BARD AHL
Product code : 1105-11201 735110R7

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Consumer use

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

SADAPS BARD AHL Additives & Lubricants
ZI TOURNAI OUEST 2 - RUE DU MONT DES CARLIERS, 3
7522 TOURNAI - BELGIQUE
T +32 (0).69.59.03.60 - F +32 (0).69.59.03.61
msds@bardahlfrance.com - www.bardahlfrance.com

1.4. Emergency telephone number

Emergency number : + 32 (0)70.245.245 / +33 (0)1.45.42.59.59

Country	Organisation/Company	Address	Emergency number	Comment
Greece	Poisons Information Centre Children's Hospital "Aglaia. Kyriakou"	11527 Athens	+30 10 779 3777	
Malta	Medicines & Poisons Info Office	Mater Dei Hospital MSD Msida	+356 2545 6504	
United Kingdom	National Poisons Information Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA Belfast	0844 892 0111 (UK only, Monday to Friday, 08.00 to 18.00 hours)	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Precautionary statements (CLP) : P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER/doctor
P501 - Dispose of contents/container in accordance with local regulations

EUH-statements : EUH208 - Contains Calcium long chain alkaryl sulphonate.. May produce an allergic reaction

2.3. Other hazards

Other hazards not contributing to the classification : Note L : The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method', Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

ENGINE STOP LEAK BARDAHL

Safety Data Sheet

3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
xylene (Note C)	(CAS No) 1330-20-7 (EC no) 215-535-7 (EC index no) 601-022-00-9 (REACH-no) 01-2119488216-32	< 5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
Polyolefin polyamine succinimide, polyol	(EC no) polymer	< 2,5	Aquatic Chronic 4, H413
Calcium long chain alkaryl sulphonate.	(EC no) polymer	< 1	Skin Sens. 1, H317 Aquatic Chronic 4, H413
Alkylphenol ramifié et un alkylphénol ramifié de calcium	(CAS No) polymer (EC no) BAP (EC index no) CABAP	< 0,15	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Repr. 1B, H360 Aquatic Chronic 1, H410

Note C : Certaines substances organiques peuvent être commercialisées soit sous une forme isomérique bien définie, soit sous forme de mélange de plusieurs isomères. Dans ces cas-là, le fournisseur doit préciser sur l'étiquette si la substance est un isomère spécifique ou un mélange d'isomères.

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Allow breathing of fresh air. Allow the victim to rest. Obtain medical attention if breathing difficulty persists.
First-aid measures after skin contact	: Wash with plenty of soap and water. Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persist.
First-aid measures after ingestion	: Do NOT induce vomiting. Obtain emergency medical attention. Rinse mouth. Call a POISON CENTER or doctor/physician if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/injuries after eye contact	: Direct contact with the eyes is likely to be irritating.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Carbon dioxide. Dry powder. Sand. Foam.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.
-------------	---

5.3. Advice for firefighters

Precautionary measures fire	: Do not enter fire area without proper protective equipment, including respiratory protection.
Firefighting instructions	: Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Keep public away from danger area. Equip cleanup crew with proper protection.
------------------	---

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

ENGINE STOP LEAK BARD AHL

Safety Data Sheet

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not eat, drink or smoke when using this product. Provide good ventilation in process area to prevent formation of vapour.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a dry place. Store in original container. Keep container closed when not in use.

Incompatible products : Oxidizing agent.

Maximum storage period : 60 months

Storage temperature : 15 - 30 °C

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

PPG-2 METHYL ETHER (34590-94-8)		
France	VME (mg/m ³)	308 mg/m ³
France	VME (ppm)	50 ppm
France	VME (mg/m ³)	5 mg/m ³
France	VLE (mg/m ³)	10 mg/m ³
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)		
France	VME (mg/m ³)	7 (8h)
France	VME (ppm)	5 ppm (8h)
France	VLE (mg/m ³)	14 mg/m ³ (15m)
France	VLE (ppm)	10 ppm (15m)
xylene (1330-20-7)		
Belgium	Limit value (mg/m ³)	221 mg/m ³
Belgium	Limit value (ppm)	50 ppm
Belgium	Short time value (mg/m ³)	100 mg/m ³
Belgium	Short time value (ppm)	442 ppm
ethylbenzene (100-41-4)		
Belgium	Limit value (mg/m ³)	440 mg/m ³
Belgium	Limit value (ppm)	100 ppm
Belgium	Short time value (mg/m ³)	551 mg/m ³
Belgium	Short time value (ppm)	125 ppm

8.2. Exposure controls

Personal protective equipment : Avoid all unnecessary exposure.

ENGINE STOP LEAK BARD AHL

Safety Data Sheet

Hand protection	: Wear suitable gloves tested to EN374. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer
Eye protection	: Avoid contact with eyes. Chemical goggles or safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: In case of inadequate ventilation wear respiratory protection



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: red.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 65 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 0,87 - 0,88
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions.

10.2. Chemical stability

Product is stable.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Heat. Open flame. Sparks. Direct sunlight.

10.5. Incompatible materials

Oxidizing agent.

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide. hydrocarbons. fume.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
----------------	------------------

ENGINE STOP LEAK BARDAHL

Safety Data Sheet

PPG-2 METHYL ETHER (34590-94-8)	
LD50 oral rat	5135 mg/kg
LD50 dermal rabbit	9510 mg/kg
LC50 inhalation rat (mg/l)	3,35 mg/l
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 inhalation rat (Dust/Mist - mg/l/4h)	5,53 mg/l/4h
xylene (1330-20-7)	
LD50 oral rat	4300 mg/kg
LC50 inhalation rat (mg/l)	28,1 mg/l
ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	5000 mg/kg
Skin corrosion/irritation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Serious eye damage/irritation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Respiratory or skin sensitisation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Not classified Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Specific target organ toxicity (single exposure)	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Potential adverse human health effects and symptoms	: No data available.

SECTION 12: Ecological information

12.1. Toxicity

PPG-2 METHYL ETHER (34590-94-8)	
LC50 fish 1	> 1000 mg/l
EC50 Daphnia 1	1919 mg/l
xylene (1330-20-7)	
LC50 fish 1	2,6 - 13,5 mg/l
EC50 Daphnia 1	1 ml/l
ethylbenzene (100-41-4)	
LC50 fish 1	4,2 mg/l

12.2. Persistence and degradability

ENGINE STOP LEAK BARDAHL	
Persistence and degradability	Not established.
PPG-2 METHYL ETHER (34590-94-8)	
Biodegradation	75 %

12.3. Bioaccumulative potential

ENGINE STOP LEAK BARDAHL	
Bioaccumulative potential	Not established.
PPG-2 METHYL ETHER (34590-94-8)	
Log Pow	1,01
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
Log Pow	> 3

ENGINE STOP LEAK BARD AHL

Safety Data Sheet

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Additional information : Avoid release to the environment

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations : Do not discharge into drains or the environment.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

14.6. Special precautions for user

- Overland transport

Not regulated

- Transport by sea

Not regulated

- Air transport

Not regulated

- Inland waterway transport

Not regulated

- Rail transport

Not regulated

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations

France

ENGINE STOP LEAK BARDAHL

Safety Data Sheet

Occupational diseases : RG 84 - Affections engendrées par les solvants organiques liquides à usage professionnel
RG 49 - Affections cutanées provoquées par les amines aliphatiques, alicycliques ou les éthanolamines
RG 4 BIS - Affections gastro-intestinales provoquées par le benzène, le toluène, les xylènes et tous les produits en renfermant
RG 36 - Affections provoquées par les huiles et graisses d'origine minérale ou de synthèse
RG 65 - Lésions eczématiformes de mécanisme allergique

Germany

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed
SZW-lijst van mutagene stoffen : None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : xylene is listed

Denmark

Class for fire hazard : Class III-1
Store unit : 50 liter
Classification remarks : Flammable according to the Danish Ministry of Justice; Emergency management guidelines for the storage of flammable liquids must be followed
Recommendations Danish Regulation : Pregnant/breastfeeding women working with the product must not be in direct contact with the product
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Repr. 1B	Reproductive toxicity, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H226	Flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H360	May damage fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H410	Very toxic to aquatic life with long lasting effects

ENGINE STOP LEAK BARDAHL

Safety Data Sheet

H413	May cause long lasting harmful effects to aquatic life
EUH208	Contains . May produce an allergic reaction

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product