



XTS 0W30

DESCRIPTION

Fully synthetic engine oil formulated with last generation performance additives to reduce friction, eliminate sludge and optimize fuel consumption. Offers a good general protection of the engine.

APPLICATION

Bardahl XTS 0w30 provides excellent performance at low temperature. It has been developed to meet the requirements of the Volkswagen « Longlife 2 » programme. It is a fuel economy engine oil. **It is not suitable for engines requiring a VW 503.01 performance level.**

SPECIFICATIONS

This product offers the following performance level:

ACEA	A1/B1-04 A5/B5-04
VW	503.00/506.00/506.01

PROPERTIES

- ✓ Fuel economy engine oil.
- ✓ Offers a stable viscosity and a high Viscosity Index.
- ✓ Extends the oil drain interval.
- ✓ Offers excellent dispersion and detergency properties.
- ✓ Forms a protective lubricating film at high temperature.
- ✓ Makes cold start easier.
- ✓ Provides a good resistance against « shearing ».
- ✓ Contains anti-corrosion, anti-wear and anti-foam additives.

SADAPS BARD AHL ADDITIVES & LUBRICANTS



XTS 0W30

TECHNICAL DATA

Density at à 15 °C	Kg/l	0,857
Viscosity at -30 °C	mPa.s	3100
Viscosity at 40 °C	mm2/s	55,30
Viscosity at 100 °C	mm2/s	10,10
Viscosity Index		174
Flash point COC, °C	°C	226
Pour point, °C	°C	-50
TBN alcalinity	mgKOH/g	10,2
Sulphated ash contents	%	1,28

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 36 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

36130	6 x 400 ML
36131	12 x 1 L
36133	3 x 5 L
36134	60 L

SADAPS BARDAHL ADDITIVES & LUBRICANTS