



TECHNICAL DATA SHEET  
V052017

# XTEC 0W20 V

## DESCRIPTION

New generation fully synthetic engine oil developed to avoid fuel overconsumption. Formulated from the latest generation performance additives.

## APPLICATION

**Bardahl XTEC 0w20 V** improves the consumption of the fuel, allows for a higher resistance to shearing. Bardahl XTEC 0w20 V is particularly suitable for Volvo diesel and petrol engines.

## SPECIFICATIONS

This product offers the following performance level:

ACEA	C5
VOLVO	VCC RBS0-2AE

## PROPERTIES

- ✓ Avoids fuel overconsumption,
- ✓ Good resistance against shearing,
- ✓ Offers excellent dispersion and detergency properties,
- ✓ Makes cold starting easier even at very low temperature (-40°C),
- ✓ Anti-foam,
- ✓ Anti-wear,
- ✓ Anti-corrosion,
- ✓ High and stable viscosity index.

### SADAPS BARD AHL ADDITIVES & LUBRICANTS

ZI Tournai Ouest - 3, Rue du Mont des Carliers - B-7522 TOURNAI  
Tél. : +32 69 590 360 - Fax : +32 69 590 361 - [www.bardahlfrance.com](http://www.bardahlfrance.com)



TECHNICAL DATA SHEET  
V052017

**TECHNICAL DATA**

Density at 15°C	Kg/l	0,843
Viscosity at -35°C	mPa.s	5570
Viscosity at 40°C	mm <sup>2</sup> /s	45,90
Viscosity at 100°C	mm <sup>2</sup> /s	8,7
Viscosity index		173
Flash point COC, °C	°C	220
Pour point, °C	°C	-45
TBN alkalinity	mgKOH/g	7,7
Sulphated ash contents	%	0,8

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

**RECOMMENDATIONS**

Handling: any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

**REFERENCES & AVAILABILITIES**

REF 36811	12 X 1L
REF 36813	3 X 5 L
REF 36817	20L
REF 36814	60L
REF 36818	205L

**SADAPS BARD AHL ADDITIVES & LUBRICANTS**

ZI Tournai Ouest - 3, Rue du Mont des Carliers - B-7522 TOURNAI  
Tél. : +32 69 590 360 - Fax : +32 69 590 361 - [www.bardahlfrance.com](http://www.bardahlfrance.com)