



SAFETY DATA SHEET

Page : 1 / 8

Revised edition no : 9

Date : 12 / 6 / 2015

Supersedes : 17 / 5 / 2013

LUBRICATING PENETRATING OIL BARD AHL

1121-1123



2.1 : flammable gas.

Danger



SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Identification of the product : Aerosols dispensers.
Trade name : LUBRICATING PENETRATING OIL BARD AHL

1.2. Relevant identified uses of the substance or mixture and uses advised against

See product bulletin for detailed information.

1.3. Details of the supplier of the safety data sheet

Producer/Manufacturer : SADAPS BARD AHL Additives & Lubricants
ZI TOURNAI OUEST 2
RUE DU MONT DES CARLIERS, 3
7522 TOURNAI Belgique-Belgie
TEL : +32 (0).69.59.03.60
FAX : +32 (0).69.59.03.61
MAIL : msds@bardahlfrance.com

Distributor : SADAPS BARD AHL CORPORATION
BP 50050 MOUVAUX
59589 BONDUES Cedex France
TEL : +33 (0)3 10 38 38 38
FAX : +33 (0)3 20 82 97 87
MAIL : msds@bardahlfrance.com

1.4. Emergency telephone number

+32 (0)70.245.245
+33 (0)1.45.42.59.59

SECTION 2 Hazards identification

2.1. Classification of the substance or mixture

Hazard Class and Category Code Regulation EC 1272/2008 (CLP)

• Supplemental hazard information : EUH066 - Repeated exposure may cause skin dryness or cracking.

SADAPS BARD AHL Additives & Lubricants

ZI TOURNAI OUEST 2 RUE DU MONT DES CARLIERS, 3 7522 TOURNAI Belgique-Belgie
TEL : +32 (0).69.59.03.60
FAX : +32 (0).69.59.03.61
MAIL : msds@bardahlfrance.com

In case of emergency : +32 (0)70.245.245



SAFETY DATA SHEET

Page : 2 / 8

Revised edition no : 9

Date : 12 / 6 / 2015

Supersedes : 17 / 5 / 2013

LUBRICATING PENETRATING OIL BARD AHL

1121-1123

SECTION 2 Hazards identification (continued)

- **Physical hazards** : Flammable aerosols - Category 1 - Danger (CLP : Flam. Aerosol 1)
Pressurised container: May burst if heated.
 - **Environmental hazards** : Hazardous to the aquatic environment - Chronic hazard - Category 3 (CLP : Aquatic Chronic 3)
- Text of H-Phrases :** : SECTION 16

2.2. Label elements

Labelling Regulation EC 1272/2008 (CLP)

• Hazard pictograms



- **Hazard pictograms code** : SGH02
- **Signal words** : Danger
- **Hazard statements** : H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H412 - Harmful to aquatic life with long lasting effects.
- **Supplemental hazard information** : EUH066 - Repeated exposure may cause skin dryness or cracking.
- **Precautionary statements**
 - **General** : P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
 - **Prevention** : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P260 - Do not breathe gas/spray.
P262 - Do not get in eyes, on skin, or on clothing.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
 - **Response** : P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER/doctor.
 - **Storage** : P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122oF.
 - **Disposal considerations** : P501 - Dispose of contents/container in accordance with local regulations.
- **Contains** : Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) May produce an allergic reaction.

2.3. Other hazards

None under normal conditions.

SECTION 3 Identification of the substance/mixture and of the company/undertaking

Substance name	Contents	CAS No	EC No	Annex No	REACH	Classification
Butane	: 25 - 40 %	106-97-8	203-448-7	601-004-00-0	01-2119474691-32-XXXX	F+, R12 Flam. Gas 1 (H220)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	: 20 - 30 %	64742-48-9	918-481-9	-----	01-2119457273-39-XXXX	Xn; R65 R66 Asp. Tox 1 (H304) (EUH066)
oleic acid, compound with (Z)-N-octadec-9-enylpropane-1,3-diamine	: < 2.5 %	40027-38-1	254-754-2	NOT LISTED	----	Xn; R48/22 Xi; R36/38 N; R50-53 Eye irrit 2 (H319) Skin Irrit. 2 (H315)

SADAPS BARD AHL Additives & Lubricants

ZI TOURNAI OUEST 2 RUE DU MONT DES CARLIERS, 3 7522 TOURNAI Belgique-Belgie

TEL : +32 (0).69.59.03.60

FAX : +32 (0).69.59.03.61

MAIL : msds@bardahlfrance.com

In case of emergency : +32 (0)70.245.245



SAFETY DATA SHEET

Page : 3 / 8

Revised edition no : 9

Date : 12 / 6 / 2015

Supersedes : 17 / 5 / 2013

LUBRICATING PENETRATING OIL BARD AHL

1121-1123

SECTION 3 Identification of the substance/mixture and of the company/undertaking (continued)

Reaction products of bis(4-methylpentan-2-yl) dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)

: < 1 %

----- 931-384-6

- 01-2119493620-38-XXXX

STOT RE 2 (H373)
Aquatic Acute 1 (H400)
Aquatic Chronic 2 (H411)Xn; R22
Xi; R41
R43
N; R51-53-----
Eye Dam 1 (H318)
Flam. Liq. 3 (H226)
Acute Tox. 4 (H302)
Skin Sens. 1 (H317)
Aquatic Chronic 2 (H411)

SECTION 4. First aid measures

4.1. Description of first aid measures

First aid measures

- Inhalation : Assure fresh air breathing.
- Skin contact : Wash skin thoroughly with mild soap and water.
- Eye contact : Rinse immediately with plenty of water.
- Ingestion : Not expected to be a primary route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

- Inhalation : Inhalation of vapours may cause respiratory irritation.
- Skin contact : Repeated exposure may cause skin dryness or cracking.
- Eye contact : Direct contact with the eyes is likely irritating.
- Ingestion : Ingestion unlikely.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5. Fire-fighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Carbon dioxide. Powder. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Incomplete combustion will generate poisonous carbon monoxide, carbon dioxide and other toxic gases.

5.3. Advice for fire-fighters

Wear self-contained breathing apparatus, rubber boots and thick rubber gloves.

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General precautions : Remove ignition sources.
- Personal precautions : Keep public away from danger area. Equip cleanup crew with proper protection.

6.2. Environmental precautions

SADAPS BARD AHL Additives & Lubricants

ZI TOURNAI OUEST 2 RUE DU MONT DES CARLIERS, 3 7522 TOURNAI Belgique-Belgie

TEL : +32 (0).69.59.03.60

FAX : +32 (0).69.59.03.61

MAIL : msds@bardahlfrance.com

In case of emergency : +32 (0)70.245.245



SAFETY DATA SHEET

Page : 4 / 8

Revised edition no : 9

Date : 12 / 6 / 2015

Supersedes : 17 / 5 / 2013

LUBRICATING PENETRATING OIL BARD AHL

1121-1123

SECTION 6. Accidental release measures (continued)

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Clean up methods

- on soil : Clean up any spills as soon as possible, using an absorbent material to collect it.
- on water : Take up large spills with pump or vacuum.

6.4. Reference to other sections

No data available.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

- General** : When using, do not eat, drink or smoke. Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work. Take off immediately all contaminated clothing.
- Handling** : No smoking. Do not breathe gas, fumes, vapour or spray. Wear suitable protective clothing.

7.2. Conditions for safe storage, including any incompatibilities

- Storage** : Store in dry, cool, well-ventilated area. Keep in original containers.
- Storage life** : 3 years.

7.3. Specific end use(s)

No data available.

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

- Occupational Exposure Limits** : Butane : TLV[©] -TWA [ppm] : (MAK) 1000
Butane : TLV[©] -TWA [ppm] : (ACGIH) 1000
Butane : VME [ppm] : (France) 800
Butane : VME [mg/m³] : (France) 1900
Butane : VME [mg/m³] : (allemagne) 4(II) DFG 2400
Butane : VME [mL/m³] : (allemagne) 4(II) DFG 1000
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics : VME [mg/m³] : 1200
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics : VME [ppm] : 184
Brouillards d'huile : VME [mg/m³] : (8 heures) 5
Brouillards d'huile : VLE [mg/m³] : (15 min) 10

8.2. Exposure controls

Personal protection

- Eye protection : Avoid contact with eyes.
- Skin protection : Wear suitable protective clothing.
- Hand protection : In case of repeated or prolonged contact wear gloves.(EN374)
- Respiratory protection : Where excessive vapour may result, wear approved mask.



SAFETY DATA SHEET

Page : 5 / 8

Revised edition no : 9

Date : 12 / 6 / 2015

Supersedes : 17 / 5 / 2013

LUBRICATING PENETRATING OIL BARD AHL

1121-1123

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state at 20 °C	: Liquid.
Colour	: Characteristic.
Odour	: Hydrocarbon.
• Odour threshold	: No data available.
• pH	: Not applicable.
• Melting point / Freezing point	: No data available.
• Initial boiling point - boiling range [°C]	: No data available.
Final boiling point [°C]	: No data available.
• Flash point [°C]	: <0
• Evaporation rate	: No data available.
• Flammability	: No data available.
• Explosion limits (lower - upper)	: No data available.
• Vapour pressure	: No data available.
• Vapour density	: No data available.
• Relative density	: 0.86 - 0.87
• Solubility	: Material insoluble in water.
• Partition coefficient : n-octanol / water	: No data available.
• Auto-ignition temperature	: > 230
• Thermal decomposition	: No data available.
• Viscosity	: <20 mm ² /s(40°C)
• Explosive Properties	: No data available.
• Oxidising properties	: No data available.

9.2. Other information

Other data : No data available.

SECTION 10. Stability and reactivity

10.1. Reactivity

Stable.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

None under normal conditions.

10.4. Conditions to avoid

Conditions to avoid : Open flame. Sparks. Heat.

10.5. Incompatible materials

Materials to avoid : Strong oxidizers.

10.6. Hazardous decomposition products

Hazardous decomposition products : Hydrocarbon. Carbon monoxide. Carbon dioxide.



SAFETY DATA SHEET

Page : 6 / 8

Revised edition no : 9

Date : 12 / 6 / 2015

Supersedes : 17 / 5 / 2013

LUBRICATING PENETRATING OIL BARD AHL

1121-1123

SECTION 11. Toxicological information

11.1. Information on toxicological effects

SECTION 1

Refer to Summary of hazards

Acute toxicity

- Dermal

: The substance (931-384-6) has been tested and does not cause sensitization by skin contact (H317) for a content below 9.39% (m / m).

SECTION 12. Ecological information

12.1. Toxicity

LC50-96 Hour - fish [mg/kg] : CAS 40027-38-1 = 1.34

12.2. Persistence - degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

SECTION 14. Transport information

14.1. UN Number

UN No. : 1950

14.2. Proper shipping name

UN1950 AEROSOLS, flammable (Butane), 2.1, 5F, (D)

14.3. Transport Hazard Classification

19 - Labelling ADR



: 2.1 : flammable gas.

ADR/RID

: Group : F
Class : 2

SADAPS BARD AHL Additives & Lubricants


ZI TOURNAI OUEST 2 RUE DU MONT DES CARLIERS, 3 7522 TOURNAI Belgique-Belgie

TEL : +32 (0).69.59.03.60

FAX : +32 (0).69.59.03.61

MAIL : msds@bardahlfrance.com

In case of emergency : +32 (0)70.245.245

	SAFETY DATA SHEET	Page : 7 / 8
		Revised edition no : 9
		Date : 12 / 6 / 2015
		Supersedes : 17 / 5 / 2013
LUBRICATING PENETRATING OIL BARD AHL		1121-1123

SECTION 14. Transport information (continued)

H.I. nr : --
 - Proper shipping name : UN1950 AEROSOLS, flammable (Butane), 2.1, 5F, (D)

Land transport

- ADR Class : 2
 - ADR Packing group : F

Emergency action in case of accident : No naked lights. No smoking.
 Keep public away from danger area.
 NOTIFY POLICE AND FIRE BRIGADE IMMEDIATELY.

Sea transport

- IMO-IMDG code : Class 2.1

IMO Packing group : -

- IMDG-Marine pollution : No.

- EMS-Nr : F-D S-U

Air transport

- ICAO/IATA : Packaging instructions cargo : 203
 Packaging instructions passenger: 203

- Proper shipping name : AEROSOLS, flammable

- IATA - Class or division : 2

14.4. Packing group

F

14.5. Environmental hazards

In case of spillage and/or leakage : Clean up even minor leaks or spills if possible without unnecessary risk.

14.6. Special precautions for user

Personal precautions : The driver shall not attempt to deal with any fire of the load.

Emergency action in case of accident : Stop the engine. No naked lights. No smoking. Mark roads and warns other road users. Keep public away from danger area. NOTIFY POLICE AND FIRE BRIGADE IMMEDIATELY.

14.7. Bulk transport - annex II Marpol 73/78 - IBC

No data available.

SECTION 15. Regulatory information


15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ensure all national/local regulations are observed.

: RG 65 Table: Injury mechanism allergic eczema. (FRANCE)
 Table RG 36: Diseases caused by oils and fats mineral or synthetic. (FRANCE)
 RG 49 Table : Skin disorders caused by aliphatic amines, alicyclic or ethanolamines. (FRANCE)
 Table RG 84: Diseases caused by organic solvents liquid for professional use. (FRANCE)

15.2. Chemical Safety Assessment

No data available.

	SAFETY DATA SHEET	Page : 8 / 8
		Revised edition no : 9
		Date : 12 / 6 / 2015
		Supersedes : 17 / 5 / 2013
LUBRICATING PENETRATING OIL BARD AHL		1121-1123

SECTION 16. Other information

Text of H-Phrases :	: EUH066 - Repeated exposure may cause skin dryness or cracking. H220 - Extremely flammable gas. H226 - Flammable liquid and vapour. H302 - Harmful if swallowed. H304 - May be fatal if swallowed and enters airways. H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H318 - Causes serious eye damage. H319 - Causes serious eye irritation. H373 - May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>. H400 - Very toxic to aquatic life. H411 - Toxic to aquatic life with long lasting effects.
Text of R-Phrases :	: R12 : Extremely flammable. R22 : Harmful if swallowed. R36/38 : Irritating to eyes and skin. R41 : Risk of serious damage to eyes. R43 : May cause sensitization by skin contact. R48/22 : Harmful : danger of serious damage to health by prolonged exposure if swallowed. R50/53 : Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R51/53 : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 : Harmful : may cause lung damage if swallowed. R66 : Repeated exposure may cause skin dryness or cracking.
Recommended uses and restrictions	: See product bulletin for detailed information.
Further information	: Label : Réf 1121: 731 112 R8 Réf 1123R10 Revision - See : * Safety data sheet available for professional user on request.
Print date	: 12 / 6 / 2015

The contents and format of this SDS are in accordance with Regulation (EC) N° 453/2010 of the European Parliament and of the Council.

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

End of document