



MAROIL S.R.L.

Revision nr. 11

Dated 11/11/2015

XTC C60 10W-40

Printed on 26/11/2015

Page n. 1/13

Safety data sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: M 326
Product name: XTC C60 10W-40

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Lubrificante per motori 4 tempi per auto

1.3. Details of the supplier of the safety data sheet

Name: MAROIL S.R.L.
Full address: LOC. PONTE ALLA CILIEGIA
District and Country: 55011 MARGINONE ALTOPASCIO (LU)
ITALIA
Tel. 0583/28731
Fax 0583/286542

e-mail address of the competent person responsible for the Safety Data Sheet: marco@bardahl.it

1.4. Emergency telephone number

For urgent inquiries refer to

Numeri telefonici dei principali Centri Antiveleni italiani (attivi 24/24 ore)

Centro Antiveleni di Pavia 0382 24444 (CAV IRCCS Fondazione Maugeri - Pavia)

Centro Antiveleni di Milano 02 66101029 (CAV Ospedale Niguarda Ca` Granda - Milano)

Centro Antiveleni di Bergamo 800 883300 (CAV Ospedali Riuniti - Bergamo)

Centro Antiveleni di Firenze 055 7947819 (CAV Ospedale Careggi - Firenze)

Centro Antiveleni di Roma 06 3054343 (CAV Policlinico Gemelli - Roma)

Centro Antiveleni di Roma 06 49978000 (CAV Policlinico Umberto I - Roma)

Centro Antiveleni di Napoli 081 7472870 (CAV Ospedale Cardarelli - Napoli)

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Eye irritation, category 2	H319	Causes serious eye irritation.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.



MAROIL S.R.L.

Revision nr. 11

Dated 11/11/2015

XTC C60 10W-40

Printed on 26/11/2015

Page n. 2/13



Signal words: Warning

Hazard statements:

H319 Causes serious eye irritation.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P264 Wash . . . thoroughly after handling.
P273 Avoid release to the environment.
P280 Wear eye protection / face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists: Get medical advice / attention.
P501 Dispose of contents / container to . . .

2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients.

3.1. Substances.

Information not relevant.

3.2. Mixtures.

Contains:

Identification.	Conc. %.	Classification 1272/2008 (CLP).
Distillates (petroleum), hydrotreated heavy paraffinic		
CAS. 64742-54-7	8 - 9	Asp. Tox. 1 H304
EC. 265-157-1		
INDEX. -		
Reg. no. 01-2119484627-25		
Olio minerale		
CAS. -	3,5 - 4	Asp. Tox. 1 H304
EC. Miscela		
INDEX. -		



Reg. no. Non disponibile

Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Pr) esters, zinc salts

CAS. 84605-29-8

1 - 1,5

Eye Dam. 1 H318, Skin Irrit. 2 H315, Aquatic Chronic 2 H411

EC. 283-392-8

INDEX. -

Reg. no. 01-2119493626-26

Reaction products of Benzeneamine, N-phenyl-with nonene (branched)

CAS. 36878-20-3

1 - 1,5

Aquatic Chronic 4 H413

EC. 253-249-4

INDEX. -

Reg. no. 01-2119488911-28

Phenol, dodecyl-, branched

CAS. 121158-58-5

0,1 - 0,15

Repr. 2 H361, Repr. 2 H361f, Eye Irrit. 2 H319, Skin Irrit. 2 H315, Aquatic Acute 1 H400 M=10, Aquatic Chronic 1 H410

EC. 310-154-3

INDEX. -

Reg. no. 01-2119513207-49

Difenilamina

CAS. 122-39-4

0,1 - 0,15

Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox. 3 H331, STOT RE 2 H373, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410

EC. 204-539-4

INDEX. 612-026-00-5

2,6-Di-tert-butylphenol

CAS. 128-39-2

0,1 - 0,15

Skin Irrit. 2 H315, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410

EC. 204-884-0

INDEX. -

Reg. no. 01-2119490822-33

Note: Upper limit is not included into the range.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures.

4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a



MAROIL S.R.L.

Revision nr. 11

Dated 11/11/2015

XTC C60 10W-40

Printed on 26/11/2015

Page n. 4/13

doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions.



MAROIL S.R.L.

Revision nr. 11

Dated 11/11/2015

XTC C60 10W-40

Printed on 26/11/2015

Page n. 5/13

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s).

Information not available.

SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

Regulatory References:

CZE	Česká Republika	Nařízení vlády č. 361/2007 Sb. kterým se stanoví podmínky ochrany zdraví při práci
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2015
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GRB	United Kingdom	EH40/2005 Workplace exposure limits
GRC	Ελλάδα	ΕΦΗΜΕΡΙΣ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ -ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 19 - 9 Φεβρουαρίου 2012

Difenilamina



MAROIL S.R.L.

Revision nr. 11

Dated 11/11/2015

XTC C60 10W-40

Printed on 26/11/2015

Page n. 6/13

Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
TLV	CZE	10		20	
VLA	ESP	10			
VLEP	FRA	10			
WEL	GRB	10		20	
TLV	GRC	10		20	

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.



Appearance	liquid
Colour	yellow
Odour	characteristic
Odour threshold.	Not available.
pH.	Not available.
Melting point / freezing point.	Not available.
Initial boiling point.	Not available.
Boiling range.	Not available.
Flash point.	200 °C.
Evaporation Rate	Not available.
Flammability of solids and gases	Not available.
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	Not available.
Vapour density	Not available.
Relative density.	0,857 Kg/l
Solubility	insoluble
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	Not available.
Decomposition temperature.	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Oxidising properties	Not available.

9.2. Other information.

Viscosita a 40°C	89,8 cSt
Viscosità a 100°C	13,8 cSt

SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid.

None in particular. However the usual precautions used for chemical products should be respected.



MAROIL S.R.L.

Revision nr. 11

Dated 11/11/2015

XTC C60 10W-40

Printed on 26/11/2015

Page n. 8/13

10.5. Incompatible materials.

Information not available.

10.6. Hazardous decomposition products.

Information not available.

SECTION 11. Toxicological information.

11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

Acute effects: stinging eyes. Symptoms may include: rubescence, edema, pain and lachrymation. Ingestion may cause health problems, including stomach pain and sting, nausea and sickness.

Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Pr) esters, zinc salts

LD50 (Oral).3100 mg/kg Ratto

LD50 (Dermal).> 2002 mg/kg Ratto

LC50 (Inhalation).> 2,3 mg/l/4h Ratto

Phenol, dodecyl-, branched

LD50 (Oral).2100 mg/kg Ratto

LD50 (Dermal).15000 mg/kg Coniglio

Reaction products of Benzeneamine, N-phenyl- with nonene (branched)

LD50 (Oral).> 5000 mg/kg Ratto

LD50 (Dermal).> 2000 mg/kg Ratto

Difenilamina

LD50 (Oral).> 800 mg/kg Ratto

2,6-Di-tert-butylphenol

LD50 (Oral).> 5000 mg/kg Ratto

Distillates (petroleum), hydrotreated heavy paraffinic

LD50 (Oral).> 5000 mg/kg Ratto

LD50 (Dermal).> 2000 mg/kg Coniglio

LC50 (Inhalation).2,18 mg/l/4h Ratto

SECTION 12. Ecological information.

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity.

Phosphorodithioic acid,
mixed O,O-bis (1,3-
dimethylbutyl and iso-Pr)
esters, zinc salts

LC50 - for Fish.

46 mg/l/96h Cyprinodon variegatus



MAROIL S.R.L.

Revision nr. 11

Dated 11/11/2015

XTC C60 10W-40

Printed on 26/11/2015

Page n. 9/13

Phenol, dodecyl-, branched
LC50 - for Fish. 24 mg/l/96h Pimephales promelas
EC50 - for Crustacea. 0,037 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants. 0,15 mg/l/72h Scenedesmus subspicatus

Reaction products of
Benzeneamine, N-phenyl-
with nonene (branched)
LC50 - for Fish. > 100 mg/l/96h Brachydanio rerio
EC50 - for Crustacea. > 100 mg/l/48h Daphnia magna

2,6-Di-tert-butylphenol
LC50 - for Fish. > 0,1 mg/l/96h Pimephales promelas

12.2. Persistence and degradability.

Information not available.

12.3. Bioaccumulative potential.

Information not available.

12.4. Mobility in soil.

Information not available.

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

Information not available.

SECTION 13. Disposal considerations.

13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.



MAROIL S.R.L.

Revision nr. 11

Dated 11/11/2015

XTC C60 10W-40

Printed on 26/11/2015

Page n. 10/13

SECTION 14. Transport information.

14.1. UN number.

Not applicable.

14.2. UN proper shipping name.

Not applicable.

14.3. Transport hazard class(es).

Not applicable.

14.4. Packing group.

Not applicable.

14.5. Environmental hazards.

Not applicable.

14.6. Special precautions for user.

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code.

Information not relevant.

SECTION 15. Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso category.

None.

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.



MAROIL S.R.L.

Revision nr. 11

Dated 11/11/2015

XTC C60 10W-40

Printed on 26/11/2015

Page n. 11/13

Product.

Point. 3

Substances in Candidate List (Art. 59 REACH).

None.

Substances subject to authorisation (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Repr. 2	Reproductive toxicity, category 2
Acute Tox. 3	Acute toxicity, category 3
Asp. Tox. 1	Aspiration hazard, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
Aquatic Chronic 4	Hazardous to the aquatic environment, chronic toxicity, category 4



H361	Suspected of damaging fertility or the unborn child.
H361f	Suspected of damaging fertility.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
2. Regulation (EU) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
4. Regulation (EU) 2015/830 of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament



MAROIL S.R.L.

Revision nr. 11

Dated 11/11/2015

XTC C60 10W-40

Printed on 26/11/2015

Page n. 13/13

9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

02 / 16.