



#### AVAILABILITY

REFERENCE 1045B  
6 X 150 ML

# MANUAL GEARBOX ADDITIVE

#### PRESENTATION

**BARDAHL MANUAL GEARBOX ADDITIVE** extends the gearbox shelf life, improves its performance and facilitates gear shifting by:

- Reducing wear on gear teeth
- Lowering the operating temperature
- Reducing oxidation and protecting against corrosion
- Making gear change easier
- Reducing noise

Compatible with any manual gearbox oil.

#### INSTRUCTIONS FOR USE

Add product into the oil crankcase.

Dosage: from 10 to 20% maximum of the oil crankcase capacity, respecting the recommended oil level.

Can be mixed with all types of mineral oil, semi-synthetic, fully synthetic and Dexron.

**Can not be used in automatic transmissions.**

SAE Type	75W90
Density at 15°C kg/cm <sup>3</sup>	0.9
Viscosity at 100°C mm <sup>2</sup> /s	16
Viscosity at 40°C mm <sup>2</sup> /s	120
Viscosity index	> 140
Freezing point °C	-49
Flash point °C	> 235
Test FZG <> DIN 51384	> 12
Lead content	None
Chlorine content	None
Copper corrosion test D130	1a
API GL	4-5
MIL	L 2105C

