



AVAILABILITY

REFERENCE 4001 / 4003
24 X 300 ML

RADIATOR STOP LEAK

PRESENTATION

BARDAHL RADIATOR STOP LEAK stops and prevents leaks in the cooling system. Protects all ferrous and non ferrous metals (iron, copper, aluminium) against corrosion. It is suitable for all types of engines (diesel, petrol and GPL - 2 and 4 strokes) and all types of radiators (aluminium, plastic). It is miscible with all types of antifreeze and coolant (type C, type D and universal). It is absolutely effective and essential for the cooling system of thermal engines. Convenient to use on new and old cars.

PROPERTIES

BARDAHL RADIATOR STOP LEAK is a scientific formula conceived by our laboratories and based on chemical compounds.

- 1. It stops and prevents cracks in the engine block, cylinder head, joints and all other leaks in the cooling system (radiator, water pump,...).
- 2. Does not cover but penetrate cracks, which allows a perfect circulation of the engine coolant.
- 3. Resists high temperatures, pressures, modern car vibrations (high pressure direct injection)

Does not damage joints (including rubber ones) and aluminium cylinder heads.

Advised to be used by all important car manufacturers.

INSTRUCTIONS FOR USE

- Turn on the heating system.
- Check up and fill in, if necessary, the level of coolant.
- Shake can thoroughly and add contents to cooling system.
- Run the engine for 10 minutes allowing the product to harden and seal the leaks, and then turn off the engine.

One can treats cooling systems of up to 22 litres capacity.

