



POWER STEERING STOP LEAK

APPLICATION:

POWER STEERING STOP LEAK can be used with all the oils used in power steering systems or in automatic gearboxes meeting DEXTRON or similar requirements, except LHM.

It stops leaks and allows to add oil for the power steering.

Prevents in some cases from changing very expensive parts (valve, rack, power steering seal, pump).

PROPERTIES:

- Restores the original properties of O-ring gaskets (softens hardened or shrunk gaskets, increases their volume up to 70% and cleans gasket grooves). This allows to **stop** or **prevent** leaks in the pump, rack or valve.

- **Restores the oil performances by adding new additives** and therefore increases the service life of mechanical parts.

- Stops seepage in hose connections.

- Reduces noise and vibration.

- Resists to high temperature and pressure.

Recommended by all great car manufacturers.

Caution ! Does not repair split or broken gaskets, is not effective on paper gaskets.

INSTRUCTIONS FOR USE:

Add **BARDAHL Power steering Stop Leak** in the tank up to the maximal level authorized by the manufacturer (maximum one can of 300 ml per system)

Automatic gearbox : add the content of the can in the automatic gearbox sump (maximum 10% of its content).

Before use read carefully the safety instructions on packaging or on safety data

AVAILABILITY

REFERENCE 1755B

6 X 300 ML

