



TECHNOS C60 *exceed* 5W30

TECHNOS C60 *exceed* is a **Premium Technology** lubricant for gasoline and diesel engines of the latest generation that are equipped with post-treatment systems of exhaust gas that require lubricants with a low SAPS content.

The special additives here contained, that are characterized by a low content of sulphur, phosphorus and sulphated ashes, permit to extend the life of particulate filters (FAP and DPF) and catalyzers.

The precious synthetic bases and the special high shear stability polymers employed in the formula give **TECHNOS C60 *exceed*** extraordinary properties of resistance against thermal deterioration due to oxidation, of strength of the lubricating oil veil and of fluidity at low temperatures.

TECHNOS C60 *exceed* moreover guarantees a better control of deposits, sludge and wear, thus permitting the engine the maximum mechanic efficiency and the original high performance.

TECHNOS C60 *exceed* permits to effectively fight the wear caused by the dilution of oil with fuel and the accumulation of dirt in the motor due to the biodiesel employed in gas oil.

TECHNOS C60 *exceed* assures higher performances than traditional lubricants, better protection of the engine, improved efficiency at low temperatures and stronger resistance of oil to deterioration.

Properties

- Higher control of wear, also when oil is contaminated by fuel.
- Longer life and longer lasting cleanliness of all parts of the engine.
- Protects the efficiency of particulate filters and catalyzers.
- Easy start-up and immediate lubrication at low temperature. Helps fuel saving.
- Low evaporability, permits to limit oil consumption.
- Maximum extension of oil change intervals.
- Effectively fights the early deterioration of oil caused by biodiesel.
- Totally formulated with synthetic bases.

Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio
Partita IVA 01583810468 – Codice Fiscale / Registro Imprese 00160000477 – Cap. Soc. € 98.800,00 – R.E.A. di Lucca n. 84045



TECHNOS C60 *exceed* 5W30

PERFORMANCE LEVEL

ACEA C3 / VW 504.00-507.00
MB 229.51 / BMW Longlife 04 / PORSCHE C30

CARATTERISTICHE CHIMICO-FISICHE

Viscosity at 40°C	74,4 cSt
Viscosity at 100°C	12,4 cSt
Density at 15°C	0,852 kg/l
Viscosity Index	166
Flash Point	200°C
Pour Point	<-33°C
T.B.N.	5,9 (mg KOH/g)

The values mentioned in this chart are indicative and may vary within certain tolerances.

Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio
Partita IVA 01583810468 – Codice Fiscale / Registro Imprese 00160000477 – Cap. Soc. € 98.800,00 – R.E.A. di Lucca n. 84045