



XTG 75W80

DESCRIPTION

Extreme pressure, fully synthetic, « Total Drive Line », gear oil formulated to lubricate manual transmissions and differentials submitted to difficult operating conditions (heavy loads, high speed and temperature).

APPLICATION

Bardahl XTG 75w80 is particularly suitable for heavy loaded hypoid differentials.

SPECIFICATIONS

This product offers the following performance level:

API	GL4-GL5 MT1
ZF	TE-ML 02B/ 17B
MIL	MIL-L-2105A/B/C/D/ MIL-PRF-2105E
SAE	J2360

PROPERTIES

- ✓ Offers a very good resistance to high temperature.
- ✓ Offers very strong extreme pressure (EP) properties.
- ✓ Has a low pour point.
- ✓ Provides a high resistance against corrosion and oxidation.
- ✓ Provides anti-wear and antifoam properties.

SADAPS BARDAHL ADDITIVES & LUBRICANTS



XTG 75W80

TECHNICAL DATA

Density at 15 °C	Kg/l	0,849
Viscosity at 40 °C	mm ² /s	38,3
Viscosity at 100 °C	mm ² /s	7,31
Viscosity index		159
Flash point COC, °C	°C	194
Pour point, °C	°C	-60

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 36 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

36371	12 x 1 L
36373	3 x 5 L
36378	20 L
36374	60 L
36377	205 L

SADAPS BARDAHL ADDITIVES & LUBRICANTS