



## GEAR OIL 4005 LS 75W140

**Gear Oil 4005 LS 75W140** is a synthetic lubricant for gears, especially developed for lubricating differentials, gear boxes and axles of sports cars and commercial vehicles used in severe applications.

### Excellent Performances – Total Protection

Its extraordinary E.P. and AW properties (“Extreme Pressure” and “Anti-wear”), its special “Limited Slip” additive and its strong resistance to deterioration by use make it very suitable to be employed with traditional hypoid differentials and self-locking differentials that undergo a strong stress and with gear systems exposed to high temperatures for a long time.

Very well indicated for BMW differentials, for which “Limited Slip” lubricants are required.

- Best protection of gears against wear, strong loads and rust.
- Better transmission efficiency, better fuel economy.
- Assures longer life and cleanliness to all transmission parts.
- Good resistance against deterioration and thermal oxidation.
- Inhibits the formation of foam.
- 100% synthetic formula.

### PERFORMANCE LEVEL

API GL-5 / SAE J2360  
SAE 75W140

### CHEMICAL-PHYSICAL CHARACTERISTICS:

Viscosity at 40°C	164,9 cSt
Viscosity at 100°C	26,2 cSt
Density at 15°C	0,895 kg/l
Viscosity Index	195
Flash Point	125
Pour Point	-36

*The values mentioned in this table are only indicative and can vary within certain tolerances.*

#### Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542  
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio  
Partita IVA 01583810468 – Codice Fiscale / Registro Imprese 00160000477 – Cap. Soc. € 98.800,00 – R.E.A. di Lucca n. 84045