



Product information

Classic Motor Oil SAE 20W50

Bardahl Classic Motor Oil SAE 20W50 motor oil is developed for the lubrication of gasoline engines with or without turbocharger/ compressor. This lubricant is highly resistant to extreme temperatures, which occur in turbo chargers. Detergents avoid to form any residue on the turbo bearings.

Bardahl Classic Motor Oil SAE 20W50 oil is composed of high quality solvent refined base oils which balanced additives. The anti-wear and anti-oxidation additives serve to lubricate and protect an engine in the most diverse circumstances.

This universal (multi-fleet) oil has the following features:

1. Thanks to the correct detergents level is it compatible with elastomers seals and gaskets.
2. Provides excellent protection against wear, corrosion and foaming.
3. Through good dispensing force there will be no sludge formation.
4. Prevents buildup in hot areas of the engine by good detergency.
5. Finally, this engine has a high and stable viscosity index and low sulfate axis number.

Applications

This oil meets the strictest requirements of both gasoline (even with LPG installations), with or without a turbocharger.

Specifications

API Service SF/CC

Ref 45351

Content 1 liter

Ref 42355

Content 5 liter

Ref 45382

Content 25 liter

Ref 45386

Content 60 liter

Ref 45392

Content 210 liter

OCD Nederland BV

Maxwellstraat 41 - 2216GP Dordrecht - Postbus 9024 - 3301 AA Dordrecht

Tel (078) 6512322 - Fax (078) 6174848 - email: info@bardahl.nl - website: www.bardahl.nl **45300**