



AVAILABILITY

Packaging		Ref.
CaSE	6 x 1 L	1200
	3 x 5 L	1203
Drum	20 Litres	1208
	60 Litres	1204
	200 Litres	1207

B.D.C. - BARDAHL DIESEL COMBUSTION

APPLICATION

BARDAHL DIESEL COMBUSTION is a complete preventive diesel treatment, offering at the same time an antifreeze protection. It can be used for any type of diesel vehicle (passenger cars, vans, busses, trucks, agricultural equipment, marine engines, ...)

PROPERTIES

- Lubricates and protects the injection system
- Prevents the formation of carbon deposits on valves and allows for a better spraying of fuel into the engine by cleaning the injector nozzles.
- Reduces the harmful exhaust emissions
- Improves the cetane rate for a better combustion and a reduction of consumption
- Repels condensation water and therefore prevents the formation of bacteria which can provoke severe damage to the fuel pump.
- Protects against corrosion (ASTM D665 test) and oxidation (ASTM D2774 test).
- Offers an antifreeze protection by lowering the Limit Filterability Temperature (LFT).

TECHNICAL DATA

	NON TREATED DIESEL	DIESEL WITH 0,2% OF BDC
LFT	-12°C	-20°C
Cetane rate	52	+ 6%

INSTRUCTION FOR USE

Summer use: 1L for 1000L of diesel

Winter use: 2L for 1000L of diesel

Caution: make sure you make the treatment when the outside temperature is superior to +5°C.

The information gathered in this document is based on our current knowledge and can be altered at any time without notice based on permanent research & development. The technical data are given for information only. No liability for damage caused by the incompleteness or incorrectness will be accepted. It is under the responsibility of the user to ensure that the products are suitable for their intended use.

BARDAHL
INDUSTRY

SADAPS BARDAHL Additives & Lubricants - Zoning Tournai Ouest II - 3, rue du Mont des Carliers – 7522 TOURNAI (BELGIUM)

Tel : +32 69 590 360 - Fax : +32 69 590 361 - <http://en.bardahlfrance.fr/> - export@bardahl.be

