



XTEC 5W30 C3

DESCRIPTION

Synthetic engine oil with low ash content, "Fuel economy" formulated from last generation additives and specially developed for vehicles equipped with a particle filter (DPF), conforming to the EURO IV et EURO V norms.

APPLICATION

Bardahl XTEC 5w30 C3 has been developed according to the Mid S.A.P.S/low HTHS technology. It is a very high performance and low viscosity lubricant, formulated to reduce fuel consumption and exhaust emissions. Particularly recommended for last generation BMW, MERCEDES, PORSCHE, VW, AUDI, SEAT, SKODA, petrol or diesel engines, requiring an ACEA C3 engine oil performance level.

SPECIFICATIONS

This product offers the following performance level:

ACEA	C3
API	SP
BMW	Longlife -04
PORSCHE	C30
OPEL	OV0401547
MERCEDES-BENZ	229.31/229.52 et MB-Approval 229.51
VW	Approved under VW Standard 504.00 and 507.00

PROPERTIES

- ✓ Avoids fuel overconsumption,
- ✓ Compatible with modern catalytic converters,
- ✓ Forms a lubricating film protecting the engine at high temperature,
- ✓ Extends the drain intervals,
- ✓ Offers excellent dispersion and detergency properties,
- ✓ Makes cold starting easier,
- ✓ Offers an excellent resistance against shearing,
- ✓ Provides a high protection against corrosion, wear and the formation of foam.



TECHNICAL DATA

Density at 15°C	Kg/l	0,851
Viscosity at -35°C	mPa.s	5950
Viscosity at 40°C	mm ² /s	69,2
Viscosity at 100°C	mm ² /s	12,00
Viscosity Index		171
Flash point COC, °C	°C	230
Pour point, °C	°C	-42
TBN alcalinity	mgKOH/g	6,7
Sulphated ash contents	%	0,67

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

36301	12 x 1 L
36302	4 x 4 L
36303	3 x 5 L
36308	20 L
36304	60 L
36309	205 L