



RACING CHAIN LUB MOTO BARDAHL

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Reference number: 2810

Issue date: 06-07-16 Revision date: 20-04-26 Supersedes version of: 31-10-25 Version: 4.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : RACING CHAIN LUB MOTO BARDAHL
UFI : XT91-P361-6807-TWM1
Product code : 2810 # 730281R9
Type of product : Aerosol, Lubricants and additives
Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Consumer use
Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Distributor

SADAPS BARDAHL Additives & Lubricants
ZI TOURNAI OUEST 2 - RUE DU MONT DES CARLIERS, 3
7522 TOURNAI
BELGIQUE
T +32 (0).69.59.03.60, F +32 (0).69.59.03.61
msds@bardahlfrance.com, www.bardahl.fr

Supplier

SADAPS BARDAHL Additives & Lubricants
ZI TOURNAI OUEST 2 - RUE DU MONT DES CARLIERS, 3
7522 TOURNAI
BELGIQUE
T +32 (0).69.59.03.60, F +32 (0).69.59.03.61
msds@bardahlfrance.com, www.bardahl.fr

1.4. Emergency telephone number

Emergency number : + 32 (0)70.245.245 / +33 (0)1.45.42.59.59

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
Malta	Medicines & Poisons Info Office	Mater Dei Hospital Msida MSD 2090 Msida	112 +356 2545 6508	
Saudi Arabia	Poison Control Center-Riyadh	General Directorate of Health Affairs Medial Province	+966 112324180 +966 112324189	
United Arab Emirates	Health Authority – Abu Dhabi (HAAD) Poison & Drug Information Center (PDIC)	P.O. Box 5674	+ 800-424	
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER	+44 20 7188 7188	

RACING CHAIN LUB MOTO BARDAHL

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1	H222;H229
Skin corrosion/irritation, Category 2	H315
Aspiration hazard, Category 1	H304
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS02

GHS07

Signal word (CLP)

: Danger

Hazard statements (CLP)

: H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H315 - Causes skin irritation.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P264 - Wash hands thoroughly after handling.
P273 - Avoid release to the environment.
P280 - Wear protective gloves.
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER, a doctor.
P501 - Dispose of contents/container to a hazardous or special waste collection point.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122 °F.

Extra phrases

: Use as per instructions and specifically for this purpose.

Child-resistant fastening

: Not applicable

Tactile warning

: Not applicable

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Component	
triphenyl phosphite (101-02-0)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII vPvB: not yet assessed
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) (4259-15-8)	PBT: not yet assessed vPvB: not yet assessed
n-hexane (110-54-3)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

RACING CHAIN LUB MOTO BARD AHL

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Component	
n-hexane (110-54-3)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated light paraffinic substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, LT, LV, NL, PL, RO, SE, SI, SK); substance with a Community workplace exposure limit (Note L)	CAS-No.: 64742-55-8 EC-No.: 265-158-7 REACH-no: 01-2119487077-29	10 ≤ x % < 25	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated light paraffinic substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, LT, LV, NL, PL, RO, SE, SI, SK); substance with a Community workplace exposure limit (Note L)	CAS-No.: 64742-54-7 EC-No.: 265-157-1 REACH-no: 01-2119484627-25	10 ≤ x % < 25	Not classified
butane substance with national workplace exposure limit(s) (AT, BE, DE, DK, ES, FI, FR, GB, HU, IE, LV, PL) (Note C)(Note U)	CAS-No.: 106-97-8 EC-No.: 203-448-7 EC Index-No.: 601-004-00-0 REACH-no: 01-2119474691-32	10 ≤ x % < 25	Flam. Gas 1A, H220 Press. Gas
Hydrocarbons, C6, isoalkanes, <5% n-hexane substance with national workplace exposure limit(s) (FR)	EC-No.: 931-254-9 REACH-no: 01-2119484651-34	10 ≤ x % < 25	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
n-hexane substance listed on REACH Candidate List substance with national workplace exposure limit(s) (AT, BE, DE, DK, ES, FI, FR, GB, HU, IE, IT, LV, NL, PL, RO, SE); substance with a Community workplace exposure limit	CAS-No.: 110-54-3 EC-No.: 203-777-6 EC Index-No.: 601-037-00-0	0 ≤ x % < 1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361f STOT SE 3, H336 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Note C - Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note L - The harmonised classification as a carcinogen applies unless it can be shown that the substance contains less than 3 % of dimethyl sulphoxide extract as measured by IP 346 ("Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions – Dimethyl sulphoxide extraction refractive index method" Institute of Petroleum, London), in which case a classification in accordance with Title II of this Regulation shall be performed also for that hazard class.

Note U - When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.), Press. Gas (Liq.), Press. Gas (Ref. Liq.), Press. Gas (Diss.). Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

Product subject to CLP Annex I, item 1.1.3.7. The disclosure rules of the components is modified in this case.

RACING CHAIN LUB MOTO BARDAHL

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If medical advice is needed, have product container or label at hand.
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
First-aid measures after skin contact	: Remove contaminated clothes. Wash skin with plenty of water. Wash contaminated clothing before reuse.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Causes skin irritation.
-------------------------------------	---------------------------

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Carbon dioxide. Water spray. Dry powder. Foam.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire	: Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.

5.3. Advice for firefighters

Firefighting instructions	: Exercise caution when fighting any chemical fire.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: Prevent liquid from entering sewers, watercourses, underground or low areas.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Evacuate area. Eliminate every possible source of ignition. Ensure adequate ventilation, especially in confined areas. Keep public away from danger area. Equip cleanup crew with proper protection.
------------------	--

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Dike for recovery or absorb with appropriate material. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

RACING CHAIN LUB MOTO BARDAHL

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.3. Methods and material for containment and cleaning up

- For containment : Recover the product with absorbent material.
Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of solid materials or residues refer to section 13: "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Do not eat, drink or smoke when using this product. Provide good ventilation in process area to prevent formation of vapour. For further information refer to section 8: "Exposure controls/personal protection". Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.
Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Provide local exhaust or general room ventilation.
Storage conditions : Keep out of frost.
Heat and ignition sources : Keep away from naked flames/heat. Keep away from ignition sources. Do not expose to temperatures exceeding 50 °C/ 122 °F.
Information on mixed storage : Keep away from food, drink and animal feeding stuffs.
Storage area : Store in a well-ventilated place. Store in a dry place.
Special rules on packaging : Store in original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

butane (106-97-8)	
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	1600 mg/m ³
	800 ppm
MAK (OEL STEL)	3800 mg/m ³
	1600 ppm
Belgium - Occupational Exposure Limits	
OEL STEL	2370 mg/m ³
	980 ppm
Denmark - Occupational Exposure Limits	
8-timers grænseværdi (OEL TWA)	1200 mg/m ³
	500 ppm
Korttidsgrænseværdi (OEL STEL)	2400 mg/m ³
	1000 ppm

RACING CHAIN LUB MOTO BARDAHL

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

butane (106-97-8)	
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	1900 mg/m ³
	800 ppm
HTP (OEL STEL)	2400 mg/m ³
	1000 ppm
France - Occupational Exposure Limits	
VLEP 8h (OEL TWA)	1900 mg/m ³
	800 ppm
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	2400 mg/m ³
	1000 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	9400 mg/m ³
CK (OEL STEL)	2350 mg/m ³
Ireland - Occupational Exposure Limits	
OEL STEL	1000 mg/m ³
Latvia - Occupational Exposure Limits	
OEL TWA	300 mg/m ³
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	1900 mg/m ³
NDSP (OEL C)	3000 mg/m ³
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	1935 mg/m ³
	800 ppm
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	1450 mg/m ³
	600 ppm
WEL STEL (OEL STEL)	1810 mg/m ³
	750 ppm
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	600 mg/m ³
	250 ppm
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	1900 mg/m ³
	800 ppm
Hydrocarbons, C6, isoalkanes, <5% n-hexane	
France - Occupational Exposure Limits	
VLEP 8h (OEL TWA)	1000 mg/m ³
VLEP CT (OEL STEL)	1500 mg/m ³

RACING CHAIN LUB MOTO BARDAHL

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	5 mg/m ³
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	5 mg/m ³
Belgium - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
OEL STEL	10 mg/m ³
Bulgaria - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	5 mg/m ³
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	5 mg/m ³
NPK-P (OEL C)	10 mg/m ³
Denmark - Occupational Exposure Limits	
8-timers grænseværdi (OEL TWA)	1 mg/m ³
Kortidsgrænseværdi (OEL STEL)*	2 mg/m ³
Estonia - Occupational Exposure Limits	
OEL TWA	3 mg/m ³
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	5 mg/m ³
France - Occupational Exposure Limits	
VLEP 8h (OEL TWA)	5 mg/m ³
Germany - Occupational Exposure Limits (TRGS 552)	
Concentration limits	5 mg/m ³
Greece - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	5 mg/m ³
Ireland - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Latvia - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	1 mg/m ³
TPRV (OEL STEL)	3 mg/m ³
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	5 mg/m ³

RACING CHAIN LUB MOTO BARDAHL

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	5 mg/m ³
Romania - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
OEL STEL	10 mg/m ³
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA)	1 mg/m ³
	5 ppm
NPHV (OEL STEL)	3 mg/m ³
	15 ppm
Slovenia - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	5 mg/m ³
VLA-EC (OEL STEL)	10 mg/m ³
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	1 mg/m ³
KGV (OEL STEL)	3 mg/m ³
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	5 mg/m ³
WEL STEL (OEL STEL)*	15 mg/m ³
Iceland - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	1 mg/m ³
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	5 mg/m ³
USA - ACGIH® - Threshold Limit Values	
ACGIH® TLV® TWA	5 mg/m ³
ACGIH® TLV® STEL	10 mg/m ³
Distillates (petroleum), hydrotreated light paraffinic (64742-54-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	5 mg/m ³
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	5 mg/m ³
Belgium - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
OEL STEL	10 mg/m ³

RACING CHAIN LUB MOTO BARDAHL

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Distillates (petroleum), hydrotreated light paraffinic (64742-54-7)	
Bulgaria - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	5 mg/m ³
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	5 mg/m ³
NPK-P (OEL C)	10 mg/m ³
Denmark - Occupational Exposure Limits	
8-timers grænseværdi (OEL TWA)	1 mg/m ³
Korttidsgrænseværdi (OEL STEL)*	2 mg/m ³
Estonia - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	5 mg/m ³
France - Occupational Exposure Limits	
VLEP 8h (OEL TWA)	5 mg/m ³
Germany - Occupational Exposure Limits (TRGS 552)	
Concentration limits	5 mg/m ³
Greece - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	5 mg/m ³
Ireland - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Latvia - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	1 mg/m ³
TPRV (OEL STEL)	3 mg/m ³
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	5 mg/m ³
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	5 mg/m ³
Romania - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
OEL STEL	10 mg/m ³
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA)	1 mg/m ³
	5 ppm

RACING CHAIN LUB MOTO BARDAHL

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Distillates (petroleum), hydrotreated light paraffinic (64742-54-7)	
NPHV (OEL STEL)	3 mg/m ³
	15 ppm
Slovenia - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	5 mg/m ³
VLA-EC (OEL STEL)	10 mg/m ³
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	1 mg/m ³
KGV (OEL STEL)	3 mg/m ³
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	5 mg/m ³
WEL STEL (OEL STEL)*	15 mg/m ³
Iceland - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	1 mg/m ³
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	5 mg/m ³
USA - ACGIH® - Threshold Limit Values	
ACGIH® TLV® TWA	5 mg/m ³
ACGIH® TLV® STEL	10 mg/m ³
2-ethylhexan-1-ol (104-76-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	2-ethylhexan-1-ol
IOEL TWA	5,4 mg/m ³
	1 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	5,4 mg/m ³
	1 ppm
MAK (OEL STEL)	10,8 mg/m ³
	2 ppm
Belgium - Occupational Exposure Limits	
OEL TWA	5,4 mg/m ³
	1 ppm
Denmark - Occupational Exposure Limits	
8-timers grænseværdi (OEL TWA)	5,4 mg/m ³
	1 ppm

RACING CHAIN LUB MOTO BARDAHL

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-ethylhexan-1-ol (104-76-7)	
Korttidsgrænseværdi (OEL STEL)	10,8 mg/m ³
	2 ppm
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	5,4 mg/m ³
	1 ppm
France - Occupational Exposure Limits	
VLEP 8h (OEL TWA)	5,4 mg/m ³
	1 ppm
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	54 mg/m ³
	10 ppm
Ireland - Occupational Exposure Limits	
OEL TWA	5,4 mg/m ³
	1 ppm
Italy - Occupational Exposure Limits	
OEL TWA	5,4 mg/m ³
	1 ppm
Latvia - Occupational Exposure Limits	
OEL TWA	5,4 mg/m ³
	1 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	5,4 mg/m ³
NDSP (OEL C)	10,8 mg/m ³
Romania - Occupational Exposure Limits	
OEL TWA	5,4 mg/m ³
	1 ppm
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	5,4 mg/m ³
	1 ppm
VLA-EC (OEL STEL)	110 mg/m ³
	20 ppm
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	5,4 mg/m ³
	1 ppm
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	5,4 mg/m ³
WEL STEL (OEL STEL)*	16,2 mg/m ³
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	5,4 mg/m ³

RACING CHAIN LUB MOTO BARDAHL

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-ethylhexan-1-ol (104-76-7)	
	1 ppm
Korttidsverdi (OEL STEL)	54 mg/m ³
	10 ppm
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	5,4 mg/m ³
	1 ppm
KZGW (OEL STEL)	10,8 mg/m ³
	2 ppm
mineral oil	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	5 mg/m ³
n-hexane (110-54-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	72 mg/m ³
	20 ppm
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	72 mg/m ³
	20 ppm
MAK (OEL STEL)	288 mg/m ³
	80 ppm
Belgium - Occupational Exposure Limits	
OEL TWA	72 mg/m ³
	20 ppm
Denmark - Occupational Exposure Limits	
8-timers grænseværdi (OEL TWA)	72 mg/m ³
	20 ppm
Korttidsgrænseværdi (OEL STEL)	144 mg/m ³
	40 ppm
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	72 mg/m ³
	20 ppm
France - Occupational Exposure Limits	
VLEP 8h (OEL TWA)	72 mg/m ³
	20 ppm
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	180 mg/m ³
	50 ppm

RACING CHAIN LUB MOTO BARDAHL

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

n-hexane (110-54-3)	
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	72 mg/m ³
Ireland - Occupational Exposure Limits	
OEL TWA	72 mg/m ³
	20 ppm
Italy - Occupational Exposure Limits	
OEL TWA	72 mg/m ³
	20 ppm
Latvia - Occupational Exposure Limits	
OEL TWA	72 mg/m ³
	20 ppm
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	72 mg/m ³
TGG-15min (OEL STEL)	144 mg/m ³
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	72 mg/m ³
Romania - Occupational Exposure Limits	
OEL TWA	72 mg/m ³
	20 ppm
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	72 mg/m ³
	20 ppm
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	72 mg/m ³
	20 ppm
KGV (OEL STEL)	180 mg/m ³
	50 ppm
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	72 mg/m ³
	20 ppm
WEL STEL (OEL STEL)*	216 mg/m ³
	60 ppm
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	180 mg/m ³
	50 ppm
KZGW (OEL STEL)	1440 mg/m ³
	400 ppm

8.1.2. Recommended monitoring procedures

No additional information available

RACING CHAIN LUB MOTO BARDAHL

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No additional information available

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses. ISO 16321-1

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Skin and body protection	
Type	Standard
Use chemically protective clothing	EN 14605

Hand protection:

Gloves. ISO 374-1

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Gloves	Nitrile rubber (NBR), Polyvinylalcohol (PVA)				EN ISO 374

8.2.2.3. Respiratory protection

Respiratory protection:

Good ventilation of the workplace required. Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

No additional information available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Colour : Yellow.
Appearance : Aerosol.

RACING CHAIN LUB MOTO BARDAHL

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Odour	: Not available
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not available
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: Not applicable
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: < 7 mm ² /s (40°C)
Solubility	: insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: 110 kPa (50°C)
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: < 1
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : 20,9 %

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions. Contains gas under pressure; may explode if heated.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Heat. Open flame. Sparks. Water, humidity. Freezing.

10.5. Incompatible materials

Strong acids. Strong oxidizers.

10.6. Hazardous decomposition products

Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

RACING CHAIN LUB MOTO BARDAHL

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hydrocarbons, C6, isoalkanes, <5% n-hexane	
LD50 oral rat	≥ 5000 mg/kg
LD50 dermal rabbit	≥ 5000 mg/kg
LC50 Inhalation - Rat	> 50 mg/l/4h
LC50 Inhalation - Rat (Dust/Mist)	≥ 50 mg/l/4h
Butene, polymer with 2-methyl-1-propene (9044-17-1)	
LD50 oral rat	> 34000 mg/kg
LD50 dermal rat	> 10000 mg/kg
LC50 Inhalation - Rat	> 17 mg/m ³
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 Inhalation - Rat (Vapours)	> 5,53 mg/l/4h
Distillates (petroleum), hydrotreated light paraffinic (64742-54-7)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 Inhalation - Rat (Vapours)	> 5,53 mg/l/4h
2-ethylhexan-1-ol (104-76-7)	
LD50 oral rat	2500 mg/kg
LD50 dermal rabbit	2500 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	1,5 mg/l/4h
LC50 Inhalation - Rat (Vapours)	11 mg/l/4h
triphenyl phosphite (101-02-0)	
LD50 dermal rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: other:
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) (4259-15-8)	
LD50 oral rat	3100 mg/kg bodyweight
LD50 dermal rabbit	> 5000 mg/kg bodyweight
mineral oil	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	> 5 mg/l/4h
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
Hydrocarbons, C6, isoalkanes, <5% n-hexane	
STOT-single exposure	May cause drowsiness or dizziness.

RACING CHAIN LUB MOTO BARDAHL

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-ethylhexan-1-ol (104-76-7)	
STOT-single exposure	May cause respiratory irritation.
n-hexane (110-54-3)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
triphenyl phosphite (101-02-0)	
NOAEL (oral, rat, 90 days)	15 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
n-hexane (110-54-3)	
STOT-repeated exposure	Causes damage to organs (nervous system) through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.
RACING CHAIN LUB MOTO BARDAHL	
Vaporizer	Aerosol
Viscosity, kinematic	< 7 mm ² /s (40°C)

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

Butene, polymer with 2-methyl-1-propene (9044-17-1)	
LC50 - Fish [1]	> 1000 mg/l
EC50 - Crustacea [1]	> 1000
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
EC50 - Crustacea [1]	> 10000 mg/l
Distillates (petroleum), hydrotreated light paraffinic (64742-54-7)	
EC50 - Crustacea [1]	> 10000 mg/l
2-ethylhexan-1-ol (104-76-7)	
LC50 - Fish [1]	28,2 mg/l (Pimephales promelas, 4DY)
LC50 - Fish [2]	17,1 mg/l (Ide mélanote (Leuciscus idus), 4DY)
EC50 - Crustacea [1]	1,82 mg/l (48h)
EC50 - Crustacea [2]	2,72 mg/l (24h)
EC50 - Other aquatic organisms [1]	39 mg/l (Cladocère, 2DY)
EC50 72h - Algae [1]	16,6 mg/l Scenedesmus subspicatus
EC50 72h - Algae [2]	11,5 mg/l Desmodesmus subspicatus

RACING CHAIN LUB MOTO BARDAHL

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-ethylhexan-1-ol (104-76-7)	
EC50 96h - Algae [1]	1,3 mg/l Skeletonema costatum
NOEC chronic fish	14 mg/l (Ide mélanote (Leuciscus idus), 4DY)
triphenyl phosphite (101-02-0)	
LC50 - Fish [1]	> 12 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	0,94 mg/l (Daphnia magna)
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) (4259-15-8)	
LC50 - Fish [1]	4,4 mg/l Oncorhynchus mykiss
EC50 - Crustacea [1]	75 mg/l Daphnia magna ; 2 days
EC50 72h - Algae [1]	410 mg/l Scenedesmus quadricauda ; 3 days
NOEC chronic crustacea	0,4 mg/l (Daphnia magna), 21 d
NOEC chronic algae	220 mg/l Scenedesmus quadricauda; 3 days
mineral oil	
LC50 - Fish [1]	> 100 mg/l (Pimephales promelas)
EC50 - Crustacea [1]	> 10000 mg/l (Daphnia magna)
EC50 72h - Algae [1]	> 100 mg/l (Scenedesmus quadricauda)
NOEC chronic crustacea	> 10 mg/l (Daphnia magna) ; 21 days
12.2. Persistence and degradability	
Butene, polymer with 2-methyl-1-propene (9044-17-1)	
Persistence and degradability	Not readily biodegradable.
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
Biodegradation	31 % OECD 301F
Distillates (petroleum), hydrotreated light paraffinic (64742-54-7)	
Biodegradation	31 %
2-ethylhexan-1-ol (104-76-7)	
Persistence and degradability	Readily biodegradable.
Biodegradation	95 % (OECD TG 302 B), 100% (OECD TG 301 C)
triphenyl phosphite (101-02-0)	
Biodegradation	0,14 % OECD TG 301 D
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) (4259-15-8)	
Persistence and degradability	Not readily biodegradable. (OECD 301D method). <5 % biodegradation 28 days.
mineral oil	
Persistence and degradability	Not readily biodegradable. (OECD 301B method). 31 % biodegradation 28 days.
12.3. Bioaccumulative potential	
2-ethylhexan-1-ol (104-76-7)	
Bioconcentration factor (BCF REACH)	25,35
Partition coefficient n-octanol/water (Log Kow)	2,9

RACING CHAIN LUB MOTO BARDAHL

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

triphenyl phosphite (101-02-0)

Partition coefficient n-octanol/water (Log Kow) 6,62 (25°C)

Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) (4259-15-8)

Partition coefficient n-octanol/water (Log Kow) 3,6

12.4. Mobility in soil

2-ethylhexan-1-ol (104-76-7)

Mobility in soil -1,42

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Sewage disposal recommendations : Do not discharge into drains or the environment.

Product/Packaging disposal recommendations : Collect all waste in suitable and labelled containers and dispose according to local legislation. Dispose used or damaged aerosol cans at permitted disposal sites.





Additional information : Empty the packaging completely prior to disposal. Do not re-use empty containers.

Ecological waste information : Do not discharge the product into the environment.

European List of Waste (LoW, EC 2000/532) : 16 05 04* - gases in pressure containers (including halons) containing dangerous substances

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / RID

ADR	IMDG	IATA	RID
14.1. UN number or ID number			
UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name			
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS
Transport document description			
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1
14.3. Transport hazard class(es)			
2.1	2.1	2.1	2.1
			

RACING CHAIN LUB MOTO BARDAHL

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	RID
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available			

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

Rail transport

Classification code (RID)	: 5F
Special provisions (RID)	: 190, 327, 344, 625
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P207, LP200
Special packing provisions (RID)	: PP87, RR6, L2
Mixed packing provisions (RID)	: MP9
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W14
Special provisions for carriage - Loading, unloading and handling (RID)	: CW9, CW12

RACING CHAIN LUB MOTO BARDAHL

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Colis express (express parcels) (RID) : CE2
Hazard identification number (RID) : 23

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains substance(s) listed on the REACH Candidate List in concentrations $\geq 0.1\%$ or SCL: n-hexane (EC 203-777-6, CAS 110-54-3)

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Not listed on the Ozone Depletion list (Regulation EU 2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Seveso Directive (Disaster Risk Reduction)

Seveso III Part I (Categories of dangerous substances)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
P3a FLAMMABLE AEROSOLS 'Flammable' aerosols Category 1 or 2, containing flammable gases Category 1 or 2 or flammable liquids Category 1	150	500

Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

RACING CHAIN LUB MOTO BARD AHL

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 36	Diseases caused by oils and fats of mineral or synthetic origin
RG 59	Occupational poisoning by hexane
RG 65	Eczematiform lesions of allergic mechanism
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Employment restrictions	: Observe restrictions according Act on the Protection of Working Mothers (MuSchG). Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).
Water hazard class (WGK)	: WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1).
Override matching entry (12. BImSchV)	: Is not subject to the Major Accidents Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen	: Distillates (petroleum), hydrotreated light paraffinic, Distillates (petroleum), hydrotreated light paraffinic are listed
SZW-lijst van mutagene stoffen	: Distillates (petroleum), hydrotreated light paraffinic, Distillates (petroleum), hydrotreated light paraffinic are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid	: n-hexane is listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling	: None of the components are listed

Denmark

Danish National Regulations	: Young people below the age of 18 years are not allowed to use the product Pregnant/breastfeeding women working with the product must not be in direct contact with it. If an employee is pregnant or breastfeeding and the person in question uses or is exposed to this product at work, the employer must always carry out a risk assessment of the work. The assessment must both deal with the dangerousness of the impact and its strength and duration. The employer's decision that a pregnant or lactating woman can perform a specific work task must therefore be made in the context of her specific working conditions. See also WEA-Guideline A.1.8-7 on the working environment of pregnant and breastfeeding workers.
-----------------------------	---

Switzerland

Storage class (LK)	: LK 2 - Liquefied or pressurized gases
--------------------	---

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:	
Aerosol 1	Aerosol, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1

RACING CHAIN LUB MOTO BARDAHL

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 2	Flammable liquids, Category 2
Press. Gas	Gases under pressure
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.